




### features

- Wide-side termination (reverse-geometry) type flat chip resistor
- High reliability and performance with T.C.R.  $\pm 100 \times 10^{-6}/K$ , resistance tolerance  $\pm 0.5\%$
- Products with lead-free terminations meet EU RoHS requirements. EU RoHS regulation is not intended for Pb-glass contained in electrode, resistor element and glass.
- AEC-Q200 Tested

### dimensions and construction



Type (Inch Size Code)	Dimensions inches (mm)				
	L	W	c	d	t
<b>1E</b> (0204)	.020±.002 (0.5±0.05)	.039±.002 (1.0±0.05)	.006±.002 (0.15±0.05)	.006±.002 (0.15±0.05)	.014±.002 (0.35±0.05)
<b>1J</b> (0306)	.031±.004 (0.8±0.1)	.063±.004 (1.6±0.1)	.006±.004 (0.15±0.1)	.008±.004 (0.2±0.1)	.018±.004 (0.45±0.1)
<b>2A</b> (0508)	.049±.006 (1.25±0.15)	.079±.006 (2.0±0.15)	.012±.008 (0.3±0.2)	.014±.008 (0.35±0.2)	.022±.004 (0.55±0.1)
<b>2B</b> (0612)	.063±.006 (1.6±0.15)	.126±.008 (3.2±0.2)	.012±.008 (0.3±0.2)	.018±.006 (0.45±0.15)	.024±.004 (0.6±0.1)
<b>2H</b> (1020)	.098±.006 (2.5±0.15)	.197±.006 (5.0±0.15)	.016±.008 (0.4±0.2)	.030±.006 (0.75±0.15)	
<b>3A</b> (1225)	.122±.006 (3.1±0.15)	.252±.006 (6.3±0.15)	.018±.008 (0.45±0.2)		

### ordering information

WK73R	1J	T	TE	33L0	F
<b>Type</b>	<b>Size</b>	<b>Termination Material</b>	<b>Packaging</b>	<b>Nominal Resistance</b>	<b>Resistance Tolerance</b>
WK73R	1E: 0.33W <sup>1</sup> 1J: 0.5W <sup>1</sup> , 0.66W <sup>1</sup> 2A: 0.75W <sup>1</sup> , 1W <sup>1</sup> 2B: 0.75W <sup>1</sup> , 1.5W <sup>1</sup> 2H: 1W <sup>1</sup> , 2W <sup>1</sup> 3A: 1.5W, 3W <sup>1</sup>	T: Sn	TP: 0204: 7" 2mm pitch punched paper TD: 0306, 0508, 0612: 7" 4mm pitch punched paper TE: 1020, 1225: 7" embossed plastic For further information on packaging, please refer to Appendix A	±1%: 3 significant figures + 1 multiplier "R" indicates decimal on value <100Ω ±5%: 2 significant figures + 1 multiplier "R" indicates decimal on values <10Ω All values less than 0.1Ω (100mΩ) are expressed in mΩ with "L" as decimal. Ex: 33mΩ, 1% = 33L0	D: ±0.5% F: ±1% J: ±5%

<sup>1</sup> If you want to use at rated power use the derating curves based on the terminal part temperature on the next page.

## applications and ratings

Part Designation	Power Rating	Rated Ambient Temp.	Rated Terminal Part Temp.	T.C.R. (X 10 <sup>-6</sup> /K)	Resistance Range (Ω)			Maximum Working Voltage	Maximum Overload Voltage	Operating Temp. Range
					D±0.5% E-24/E-96	F±1% E-24/E-96	J±5% E-24			
WK73R1E (0204)	0.33W <sup>1</sup>	70°C	125°C	±100	—	10 - 1M	10 - 1M	75V	100V	-55°C to +155°C
WK73R1J (0306)	0.5W <sup>1</sup>	70°C	125°C	±100	—	10 - 1M	10 - 1M	150V	200V	
	0.66W <sup>1</sup>	—				10 - 9.76k	10 - 9.1k			
WK73R2A (0508)	0.75W <sup>1</sup>	70°C	125°C	±100	—	20.5k - 1M	22k - 1M	200V	400V	
	1.0W <sup>1</sup>	—	125°C	±100	—	10 - 20k	10 - 20k			
WK73R2B (0612)	0.75W	70°C	125°C	±100	10 - 1M	10 - 1M	10 - 1M	200V	400V	
	1.5W <sup>1</sup>	—	125°C	±100	10 - 9.76k	10 - 9.76k	10 - 9.1k			
WK73R2H (1020)	1.0W	70°C	125°C	±100	—	10 - 430k	10 - 430k	200V	400V	
				±200	—	432k - 1M	470k - 1M			
	2W <sup>1</sup>	—	125°C	±100	—	10 - 430k	10 - 430k			
		—	125°C	±200	—	432k - 1M	470k - 1M			
WK73R3A (1225)	1.5W	70°C	125°C	±100	—	10 - 330k	10 - 330k	200V	400V	
				±200	—	332k - 1M	360k - 1M			
	3W <sup>1</sup>	—	125°C	±100	—	10 - 330k	10 - 330k			
		—	125°C	±200	—	332k - 1M	360k - 1M			




Rated voltage =  $\sqrt{\text{Power rating} \times \text{resistance value}}$  or max. working voltage, whichever is lower

<sup>1</sup> If you want to use at rated power use derating curves based on the terminal part temperature on the right side graph located below.

If any questions arise whether to use the "Rated Ambient Temperature" or the "Rated Terminal Part Temperature", please give priority to the "Rated Terminal Part Temperature." For more details refer to the "Introduction of the derating curves based on the terminal part temperature" in the beginning of the catalog.

## environmental applications

### Derating Curve






For resistors operated at an ambient temperature of 70°C or above, a power rating shall be derated in accordance with the above derating curve.

When the terminal part temperature of the resistor exceeds the rated terminal part temperature shown above, the power shall be derated according to the derating curve.


Please refer to "Introduction of the derating curves based on the terminal part temperature" in the beginning of the catalog before use.

### Temperature Rise





Regarding the temperature rise, the value of the temperature varies per conditions and board for use since the temperature is measured under our measuring conditions.

#### Simulated and Measurement Conditions



Temperature rise is simulated and measured under our conditions. So, the values will vary depending on the operating conditions and PCB used.

### One-Pulse Limiting Electric Power



The maximum applicable voltage is equal to the max. overload voltage. Please ask us about the resistance characteristic of continuous applied pulse. The pulse endurance values are not assured values, so be sure to check the products on actual equipment when you use them.

### Performance Characteristics

Parameter	Requirement $\Delta R \pm(\%+0.005\Omega)$		Test Method																								
	Limit	Typical																									
Resistance	Within specified tolerance	—	25°C																								
T.C.R.	Within specified T.C.R.	—	+25°C/-55°C and +25°C/+125°C																								
Overload (Short time)	$\pm 2\%$	$\pm 0.2\%$	Overload wattage for 5s																								
			<table border="1"> <thead> <tr> <th>Type (Resistance Range/<math>\Omega</math>)</th> <th>1E</th> <th>1J</th> <th colspan="2">2A</th> <th colspan="2">2B</th> <th>2H</th> <th>3A</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td></td> <td>10~20k</td> <td>20.5k~1M</td> <td>10~10k</td> <td>10.2k~1M</td> <td></td> <td></td> </tr> <tr> <td>Overload Wattage</td> <td>1.32W</td> <td>3.125W</td> <td>4W</td> <td>3W</td> <td>6W</td> <td>4.688W</td> <td>8W</td> <td>12W</td> </tr> </tbody> </table>	Type (Resistance Range/ $\Omega$ )	1E	1J	2A		2B		2H	3A				10~20k	20.5k~1M	10~10k	10.2k~1M			Overload Wattage	1.32W	3.125W	4W	3W	6W
Type (Resistance Range/ $\Omega$ )	1E	1J	2A		2B		2H	3A																			
			10~20k	20.5k~1M	10~10k	10.2k~1M																					
Overload Wattage	1.32W	3.125W	4W	3W	6W	4.688W	8W	12W																			
Resistance to Solder Heat	$\pm 1\%$	$\pm 0.2\%$	260°C $\pm$ 5°C, 10 seconds $\pm$ 1 second																								
Bending Test	$\pm 1\%$	$\pm 0.1\%$	Holding point 90mm, Bending 1 time, Bending 5mm																								
Rapid Change of Temperature	$\pm 2\%$	$\pm 1\%$	-55°C (30 minutes) / +125°C (30 minutes), 1000 cycles																								
Moisture Resistance	$\pm 3\%$ : 1E $\pm 2\%$ : All others	$\pm 1\%$ : 1E $\pm 0.2\%$ : All others	40°C $\pm$ 2°C, 90%~95% RH, 1000 hours; 1.5 hr ON, 0.5 hr OFF cycle																								
Endurance at 70°C	$\pm 3\%$ : 1E $\pm 2\%$ : All others	$\pm 1\%$ : 1E $\pm 0.2\%$ : All others	70°C $\pm$ 2°C or rated terminal part temperature $\pm$ 2°C, 1000 hours, 1.5 hr ON, 0.5 hr OFF cycle																								
High Temperature Exposure	$\pm 1\%$	$\pm 0.2\%$	+155°C, 1000 hours																								

Additional environmental applications can also be found at [www.koaspeer.com](http://www.koaspeer.com)