### **EGG.1R.367.GLM**





Image for illustrative purpose only

## **Summary**

#### Request a quote

Catalog			
Number of contacts Low Voltage	67		
Socket / Receptacle	Socket / Receptacle - Fixed Panel Front Mounted		
Locking system	Push-pull		
Jacket cable outside diameter [mm]	2.00 - 9.20 mm		
Size	1R		
Suggested matching part	FGG.1R.367.GLC92		


### **Technical details**


### **Electrical Configuration**

Number of contacts Low Voltage	67
Contact Termination Low voltage	Crimp
Insert configuration value	1R.367 - 67 low voltage
Insulator	L: PEEK (UL 94 / V-0/1.5)
Rated current	0.5 A
Test voltage (kV rms) Contact-contact	0.6
Form & Material	
Shell style / Model id	EGG - Fixed receptacle, key (G) or key (A)
Socket / Receptacle	Fixed Panel Front Mounted
Housing material	Crastin® PBT (Polybutylene terephthalate), grey
Locking system	Push-pull
Keying	3 keys (alpha=50,beta=30, plug: male contacts, receptacle: female contacts)
Weight	15.03 g
Environment	
Environmental sealing (IP rating)	IP50
Cable fixation	
Jacket cable outside diameter [mm]	2.00 - 9.20 mm

# **Drawings**







### **Dimensions**

	A	В	L	M	
mm.	37	12.5	18	14.5	
in.	1.46	0.49	0.71	0.57	

# **Recommended By Lemo**

#### **Tools**

Positionner	DCE.91.051.BVM
Extraction tool	DCC.05.02B.LAG
Crimp tool	DPC.91.701.V