EGG.1R.803.GLM81





Image for illustrative purpose only

Summary

Request a quote

Catalog				
Number of contacts Low Voltage	3			
Nb of contacts Coax	8			
Socket / Receptacle	Socket / Receptacle - Fixed Panel Front Mount			
Locking system	Push-pull			
Jacket cable outside diameter [mm]	2.00 - 9.20 mm			
Size	1R			
Suggested matching part	FGG.1R.803.GLC8192			


Technical details


Electrical Configuration

Number of contacts Low Voltage	3
Contact Termination Low voltage	Crimp
Nb of contacts Coax	8
Insert configuration value	1R.803 - 8 Coax (50 Ohm), 3 Low V.
Insulator	L: PEEK (UL 94 / V-0/1.5)
Rated current	3 A
Impedance	50
Test voltage (kV rms)	1.5
Form & Material	
Shell style / Model id	EGG - Fixed receptacle, key (G) or key (A)
Socket / Receptacle	Fixed Panel Front Mounted
Housing material	Crastin® PBT (Polybutylene terephthalate), grey
Locking system	Push-pull
Keying	3 keys (alpha=50,beta=30, plug: male contacts, receptacle: female contacts)
Weight	24.8 g
Environment	
Environmental sealing (IP rating)	IP50
Cable fixation	
Jacket cable outside diameter [mm]	2.00 - 9.20 mm

Drawings







Dimensions

	Α	В	L	M	
mm.	37	12.5	18	14.5	
in.	1.46	0.49	0.71	0.57	

Recommended By Lemo

Accessories

Replacement contact	EGG.0B.660.ZZM	
Tools		
Positionner	DCE.91.090.BVM	
Extraction tool	DCC.09.05B.LAG	
Extraction tool 2	DCC.91.C0R.LAG	
Crimp tool	DPC.91.701.V	
Crimp Tool 2	DPE.99.003.1K	