

EMP Protector 3406.00.0030

Description

Slim Line GDT technology

Benefits

Multi-band operation
DC continuity for remote powering
The protector can also be installed reversely
Fix installed GDT, static sparkover-voltage nom. 200 V
Compliant to IEC 61643-21

Product Configuration

Main path connectors	Port 1: <u>unprotected</u> , N jack (female) - Port 2: <u>protected</u> , SMA jack (female)
Mounting and grounding	brk (bracket)
Side of bulkhead	protected side

Technical Data

Electrical Data

Impedance	50 Ω
Frequency range	0 - 3000 MHz
Return loss	≥ 20 dB
Insertion loss	≤ 0.2 dB
RF CW power	≤ 60 W
PIM 3rd order	not specified

Surge current handling capability	10 single / 5 multiple kA (test pulse 8/20 μ s)
Residual pulse energy	250 μ J typically (test pulse 4 kV 1.2/50 μ s / 2 kA 8/20 μ s) main path - protected side

Mechanical Data

Number of matings	500
Weight	70 g

Environmental Data

Operating temperature	-40 °C to +85 °C
Waterproof degree	IP65 (according to IEC 60529, data refer to the coupled state)
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant acc. Annex III

Material Data

Piece Parts	Material	Surface Plating
Housing	Stainless Steel	
Port 1 center contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Port 2 center contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)

Related Documents

Outline drawing	DOU-00178612
Mounting instruction	DOC-0000176104

Remarks

Panel mounting 5/8-24 UNEF-2B, WAF 24 mm