




Specifications:  
 Current Rating:4.5~11.5A AC/DC  
 Voltage Rating:600V AC/DC  
 Contact Resistance:10m ohm. Max.  
 Insulation Resistance:1000M ohm. Min.  
 Withstanding Voltage:1500V AC For One Minute  
 Operating Temperature Range:-40°C To +105°C

Materials:  
 Insulator:Nylon66 UL94V-0  
 Insulator Color:Transparent  
 Contact:Brass  
 Plating:Tin Plated




Dimension Information:

| Circuits | Dim A | Dim B | Circuits | Dim A | Dim B |
|----------|-------|-------|----------|-------|-------|
| 2        | 4.2   | 5.4   | 14       | 25.2  | 30.6  |
| 4        |       | 9.6   | 16       | 29.6  | 34.8  |
| 6        | 8.4   | 13.8  | 18       | 33.6  | 39.0  |
| 8        | 12.6  | 18.0  | 20       | 37.8  | 43.2  |
| 10       | 16.8  | 22.2  | 22       | 42.0  | 47.4  |
| 12       | 21.0  | 26.4  | 24       | 46.2  | 51.6  |

MAXIMUM CURRENT RATING:

| WIRE-TO-WIRE |                        |      |     |       |          |          |
|--------------|------------------------|------|-----|-------|----------|----------|
| WIRE SIZE    | Dual Row Circuit Sizes |      |     |       |          |          |
|              | 2                      | 4    | 6,8 | 10,12 | 14,16,18 | 20,22,24 |
| 16 AWG       | 12A                    | 11A  | 10A | 9.5A  | 9A       | 8.5A     |
| 18 AWG       | 10A                    | 9A   | 8A  | 7.5A  | 7A       | 6.5A     |
| 20 AWG       | 8.5A                   | 7.5A | 7A  | 6.5A  | 6A       | 5.5A     |


| WIRE-TO-BOARD |                        |       |      |       |          |          |
|---------------|------------------------|-------|------|-------|----------|----------|
| WIRE SIZE     | Dual Row Circuit Sizes |       |      |       |          |          |
|               | 2                      | 4     | 6,8  | 10,12 | 14,16,18 | 20,22,24 |
| 16 AWG        | 11.5A                  | 10.5A | 9A   | 8A    | 7.5A     | 7A       |
| 18 AWG        | 9.5A                   | 8.5A  | 7.5A | 7A    | 6.5A     | 6A       |
| 20 AWG        | 8A                     | 7A    | 6A   | 5.5A  | 5A       | 4.5A     |



RECOMMENDED P.C.B. LAYOUT

RoHS Compliant

|     |             |      |            |            |                       |                                                                          |                             |      |   |
|-----|-------------|------|------------|------------|-----------------------|--------------------------------------------------------------------------|-----------------------------|------|---|
|     |             |      |            | DRAWN:     | GENERAL TOLERANCE:    | <div>CnC Tech</div> <div>Industrial Cable and Connector Technology</div> |                             | SIZE | D |
|     |             |      |            | Jerry Chen | 30 OVER ±0.4          |                                                                          |                             |      |   |
|     |             |      |            | CHECKED:   | 10 OVER 30 UNDER ±0.3 |                                                                          |                             |      |   |
|     |             |      |            |            | 10 UNDER ±0.2         | UNIT: MM                                                                 | DESCRIPTION:                | A4   |   |
| B   | 04-Dec-2023 |      | Zongyi     |            | SCALE:1:1             |                                                                          | CONN HEADER VERT DUAL 94V-0 |      |   |
| A   | 10-Jan-2020 |      | Jerry Chen | APPROVAL:  | SHEET: 1 / 3          | PART NO:                                                                 |                             |      |   |
| REV | DATE        | FILE | BY         | Rory Chen  | PROJECTION:           | 4282-1-0100-XX-SP                                                        |                             |      |   |



2~24P Protection Key Drawing(Ref.)

RoHS Compliant

|     |             |      |            |            |                                                                                                   |                                                                          |  |                               |   |
|-----|-------------|------|------------|------------|---------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|--|-------------------------------|---|
|     |             |      |            | DRAWN:     | GENERAL TOLERANCE:                                                                                | <div>CnC Tech</div> <div>Industrial Cable and Connector Technology</div> |  | <div>SIZE</div> <div>A4</div> | D |
|     |             |      |            | Jerry Chen | 30 OVER ±0.4<br>10 OVER 30 UNDER ±0.3<br>10 UNDER ±0.2                                            |                                                                          |  |                               |   |
|     |             |      |            | CHECKED:   | UNIT: MM                                                                                          | DESCRIPTION:                                                             |  |                               |   |
| B   | 04-Dec-2023 |      | Zongyi     |            | SCALE:1:1                                                                                         | CONN HEADER VERT DUAL 94V-0                                              |  |                               |   |
| A   | 10-Jan-2020 |      | Jerry Chen | APPROVAL:  | SHEET: 2 / 3                                                                                      | PART NO:                                                                 |  |                               |   |
| REV | DATE        | FILE | BY         | Rory Chen  | PROJECTION:  | 4282-1-0100-XX-SP                                                        |  |                               |   |

