

COAXIAL FIXED ATTENUATOR, 50 Ohm, 20 dB, N

5920_N-50-050/13-_N

Properties

- Wide range of interfaces
- Fixed attenuation level from 0 dB up to 40 dB
- 50 Ω or 75 Ω impedance
- Various bandwidth to improve the impedance matching between subsystems of its waveform
- Used in many test and measurement and communication applications.

**Product configuration**

Interface	Gender	Standard
N	plug (male)	IEC 60169-16_MIL-STD-348A/304_CECC 22210
N	jack (female)	IEC 60169-16_MIL-STD-348A/304_CECC 22210

Electrical data

Impedance	50 Ω
Operating frequency	0 GHz ... 6 GHz
Attenuation nominal	20 dB
VSWR	1.25
Return loss	19.1 dB

Electrical Data (frequency related)

Frequency range	Attenuation deviation	VSWR max
0 GHz to 6 GHz	+/- 0.6 dB	1.25

Electrical Data (power)

Average power	50 W at 25 °C ambient temperature. Linearly derated to 5 W at 100 °C ambient temperature.
Peak power	1000 W, 5 μ s pulse width, 2 % duty cycle

COAXIAL FIXED ATTENUATOR, 50 Ohm, 20 dB, N

5920_N-50-050/13-_N

Interface and material data		
Interface	N / plug (male)	
Piece parts	Material	Plating
Centre contact	Brass	Gold Plating (without Nickel underplating)
Outer conductor	Brass	Tri-metal Plating
Body	Aluminium	Anodized
Insulator	PTFE (Polytetrafluoroethylene)	
Coupling nut	Brass	Tri-metal Plating
Interface	N / jack (female)	
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer conductor	Brass	Tri-metal Plating
Body	Aluminium	Anodized
Insulator	PTFE (Polytetrafluoroethylene)	

Mechanical data	
Weight	1.1 kg

Environmental data	
Operation temperature	-55 °C ... 125°C

Ordering Information Table	
Item number	Item description
85177206	5920_N-50-050/13-_NE

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver:
Facts and figures herein are for information only and do not represent any warranty of any kind.

DOCUMENT PIM-P1832 / Date of publication: 23.11.2023 / uncontrolled copy