

**COAXIAL FIXED ATTENUATOR, 50 Ohm, 30 dB, N**

5930\_N-50-025/13-\_N

**Properties**

- Wide range of interfaces
- Fixed attenuation level from 0 dB up to 40 dB
- 50  $\Omega$  or 75  $\Omega$  impedance
- Various bandwidth to improve the impedance matching between subsystems of its waveform
- Used in many test and measurement and communication applications.



Product configuration		
Interface	Gender	Standard
N	plug (male)	IEC 60169-16_MIL-STD-348A/304_CECC 22210
N	jack (female)	IEC 60169-16_MIL-STD-348A/304_CECC 22210

Electrical data	
Impedance	50 $\Omega$
Operating frequency	0 GHz ... 6 GHz
Attenuation nominal	30 dB
VSWR	1.25
Return loss	19.1 dB

Electrical Data (frequency related)		
Frequency range	Attenuation deviation	VSWR max
0 GHz to 6 GHz	+/- 0.8 dB	1.25

Electrical Data (power)	
Average power	25 W at 25 °C ambient temperature. Linearly derated to 2.5 W at 100 °C ambient temperature.
Peak power	1000 W, 5 $\mu$ s pulse width, 1 % duty cycle

**COAXIAL FIXED ATTENUATOR, 50 Ohm, 30 dB, N**

5930\_N-50-025/13-\_N

<b>Interface and material data</b>		
Interface	N / plug (male)	
<b>Piece parts</b>	<b>Material</b>	<b>Plating</b>
Centre contact	Brass	Gold Plating (without Nickel underplating)
Outer conductor	Brass	Tri-metal Plating
Body	Aluminium	Anodized
Insulator	PTFE (Polytetrafluoroethylene)	
Coupling nut	Brass	Tri-metal Plating
Interface	N / jack (female)	
<b>Piece parts</b>	<b>Material</b>	<b>Plating</b>
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer conductor	Brass	Tri-metal Plating
Body	Aluminium	Anodized
Insulator	PTFE (Polytetrafluoroethylene)	

**Mechanical data**

Weight	0.135 kg
--------	----------

**Environmental data**

Operation temperature	-55 °C ... 125°C
-----------------------	------------------

**Ordering Information Table**

Item number	Item description
85177202	5930_N-50-025/13-_NE

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.

DOCUMENT PIM-P1826 / Date of publication: 23.11.2023 / uncontrolled copy