

COAXIAL FIXED ATTENUATOR, 50 Ohm, 40 dB, N

5940_N-50-1/133_N

Properties

- Wide range of interfaces
- Fixed attenuation level from 0 dB up to 40 dB
- 50 Ω or 75 Ω impedance
- Various bandwidth to improve the impedance matching between subsystems of its waveform
- Used in many test and measurement and communication applications.



Product configuration		
Interface	Gender	Standard
N	plug (male)	IEC 60169-16_MIL-STD-348A/304_CECC 22210
N	jack (female)	IEC 60169-16_MIL-STD-348A/304_CECC 22210

Electrical data	
Impedance	50 Ω
Operating frequency	0 GHz ... 6 GHz
Attenuation nominal	40 dB
VSWR	1.45
Return loss	14.7 dB

Electrical Data (frequency related)		
Frequency range	Attenuation deviation	VSWR max
0 GHz to 1.5 GHz	+/- 1.5 dB	1.25

Electrical Data (power)	
Average power	100 W at 25 °C ambient temperature. Linearly derated to 20 W at 125 °C ambient temperature.
Peak power	1000 W, 5 μ s pulse width, 0.05 % duty cycle

COAXIAL FIXED ATTENUATOR, 50 Ohm, 40 dB, N

5940_N-50-1/133_N

Interface and material data		
Interface	N / plug (male)	
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating
Outer conductor	Stainless Steel	Passivated (Plating)
Body	Aluminium	Anodized
Insulator	PTFE (Polytetrafluoroethylene)	
Coupling nut	Stainless Steel	Passivated (Plating)
Gasket	VMQ (Silicone rubber)	
Interface	N / jack (female)	
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating
Outer conductor	Stainless Steel	Passivated (Plating)
Body	Aluminium	Anodized
Insulator	PTFE (Polytetrafluoroethylene)	

Mechanical data	
Weight	1.12 kg

Environmental data	
Operation temperature	-55 °C ... 125°C

Ordering Information Table	
Item number	Item description
85177210	5940_N-50-1/133_NE

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.

DOCUMENT PIM-P1820 / Date of publication: 13.11.2023 / uncontrolled copy