

**Surface Mount
Uni/Bi-Directional TVS Diodes****Description**

The 5.0SMDJ series is designed specifically to protect sensitive electronic equipment from voltage transients induced by lightning and other transient voltage events.

Features

- For surface mounted applications
- Low profile package
- 5000W Peak pulse power capability at 10/1000 μ s waveform
- Excellent clamping capability
- Typical IR less than 5 μ A above 20V
- Fast response time: typically less than 1.0ps from 0 Volts to VBR min

- High temperature soldering: 260°C/10s

Mechanical Data


- Case: SMC(DO-214AB) package
- Case material: "green" molding compound
- UL flammability classification rating 94V-0
- Polarity : by cathode band denotes uni-directional device, none cathode band denotes bi-directional device
- Weight: 0.28grams

Note: Products with logo  or  are made by HY Electronic (Cayman) Limited

Applications


TVS devices are ideal for the protection of I/O Interfaces, Vcc bus and other vulnerable circuits used in telecom, computer, industrial and consumer electronic applications.

Peak Pulse Power - 5000 W
Reverse Stand Off Voltage - 12 to 190 V

Package Outline Dimensions

SMC Package		
Dim	Min	Max
A	6.60	7.11
B	5.59	6.20
C	2.75	3.20
D	2.06	2.62
E	0.15	0.31
F	0.051	0.203
G	0.76	1.52
H	7.71	8.13

All Dimensions in mm

Device Schematic**Ordering Information**

- Package : SMC(DO-214AB)
- Reel Size : 13 (inches)
- Quantity Per Reel : 3Kpcs
- Quantity Per Box : 6Kpcs
- Quantity Per Carton : 48Kpcs

Maximum Ratings (@TA = +25°C, unless otherwise specified.)**Absolute Ratings**

Parameter	Symbol	Value	Unit
Peak Pulse Power Dissipation at TA=25°C by 10/1000us Waveform (Note 1)	P _{PP}	5000	W
Power Dissipation on Infinite Heat Sink at TL=50°C	P _{M(AV)}	6.5	W
Peak Forward Surge Current, 8.3ms Single Half Sine Wave (Note 2)	I _{FSM}	300	A
Operating Temperature Range	T _j	-55 to +150	°C
Storage Temperature Range	T _{STG}	-55 to +150	°C

Note:

1. Non-repetitive current pulse, per Fig.4 and derated above T_j(initial) = 25°C per Fig.1
2. For unidirectional units only



Electrical Characteristics (@TA = 25°C, unless otherwise specified.)

Part Number		Marking Code		Reverse Working Voltage VRWM(V)	Reverse Breakdown Voltage VB(V)			Reverse Leakage (Max) IR(μA) @VR	Reverse Clamping Voltage (Max) Vc(V) @IPP	Peak Pulse Current (Max) IPP(A)
					Min.	Max.	@It(mA)			
5.0SMDJ12A	5.0SMDJ12CA	5.0SMDJ12A	5.0SMDJ12CA	12	13.3	14.7	1	800	19.9	252
5.0SMDJ13A	5.0SMDJ13CA	5.0SMDJ13A	5.0SMDJ13CA	13	14.4	15.9	1	500	21.5	233
5.0SMDJ14A	5.0SMDJ14CA	5.0SMDJ14A	5.0SMDJ14CA	14	15.6	17.2	1	200	23.2	216
5.0SMDJ15A	5.0SMDJ15CA	5.0SMDJ15A	5.0SMDJ15CA	15	16.7	18.5	1	100	24.4	205
5.0SMDJ16A	5.0SMDJ16CA	5.0SMDJ16A	5.0SMDJ16CA	16	17.8	19.7	1	50	26.0	193
5.0SMDJ17A	5.0SMDJ17CA	5.0SMDJ17A	5.0SMDJ17CA	17	18.9	20.9	1	20	27.6	181
5.0SMDJ18A	5.0SMDJ18CA	5.0SMDJ18A	5.0SMDJ18CA	18	20.0	22.1	1	10	29.2	172
5.0SMDJ20A	5.0SMDJ20CA	5.0SMDJ20A	5.0SMDJ20CA	20	22.2	24.5	1	5	32.4	155
5.0SMDJ22A	5.0SMDJ22CA	5.0SMDJ22A	5.0SMDJ22CA	22	24.4	26.9	1	5	35.5	141
5.0SMDJ24A	5.0SMDJ24CA	5.0SMDJ24A	5.0SMDJ24CA	24	26.7	29.5	1	5	38.9	129
5.0SMDJ26A	5.0SMDJ26CA	5.0SMDJ26A	5.0SMDJ26CA	26	28.9	31.9	1	5	42.1	119
5.0SMDJ28A	5.0SMDJ28CA	5.0SMDJ28A	5.0SMDJ28CA	28	31.1	34.4	1	5	45.4	110
5.0SMDJ30A	5.0SMDJ30CA	5.0SMDJ30A	5.0SMDJ30CA	30	33.3	36.8	1	5	48.4	103
5.0SMDJ33A	5.0SMDJ33CA	5.0SMDJ33A	5.0SMDJ33CA	33	36.7	40.6	1	5	53.3	93.9
5.0SMDJ36A	5.0SMDJ36CA	5.0SMDJ36A	5.0SMDJ36CA	36	40.0	44.2	1	5	58.1	86.1
5.0SMDJ40A	5.0SMDJ40CA	5.0SMDJ40A	5.0SMDJ40CA	40	44.4	49.1	1	5	64.5	77.6
5.0SMDJ43A	5.0SMDJ43CA	5.0SMDJ43A	5.0SMDJ43CA	43	47.8	52.8	1	5	69.4	72.1
5.0SMDJ45A	5.0SMDJ45CA	5.0SMDJ45A	5.0SMDJ45CA	45	50.0	55.3	1	5	72.7	68.8
5.0SMDJ48A	5.0SMDJ48CA	5.0SMDJ48A	5.0SMDJ48CA	48	53.3	58.9	1	5	77.4	64.7
5.0SMDJ51A	5.0SMDJ51CA	5.0SMDJ51A	5.0SMDJ51CA	51	56.7	62.7	1	5	82.4	60.7
5.0SMDJ54A	5.0SMDJ54CA	5.0SMDJ54A	5.0SMDJ54CA	54	60.0	66.3	1	5	87.1	57.5
5.0SMDJ58A	5.0SMDJ58CA	5.0SMDJ58A	5.0SMDJ58CA	58	64.4	71.2	1	5	93.6	53.5
5.0SMDJ60A	5.0SMDJ60CA	5.0SMDJ60A	5.0SMDJ60CA	60	66.7	73.7	1	5	96.8	51.7
5.0SMDJ64A	5.0SMDJ64CA	5.0SMDJ64A	5.0SMDJ64CA	64	71.1	78.6	1	5	103	48.6
5.0SMDJ70A	5.0SMDJ70CA	5.0SMDJ70A	5.0SMDJ70CA	70	77.8	86.0	1	5	113	44.3
5.0SMDJ75A	5.0SMDJ75CA	5.0SMDJ75A	5.0SMDJ75CA	75	83.3	92.1	1	5	121	41.4
5.0SMDJ78A	5.0SMDJ78CA	5.0SMDJ78A	5.0SMDJ78CA	78	86.7	95.8	1	5	126	39.7
5.0SMDJ85A	5.0SMDJ85CA	5.0SMDJ85A	5.0SMDJ85CA	85	94.4	104.0	1	5	137	36.5
5.0SMDJ90A	5.0SMDJ90CA	5.0SMDJ90A	5.0SMDJ90CA	90	100	111	1	5	146	34.3
5.0SMDJ100A	5.0SMDJ100CA	5.0SMDJ100A	5.0SMDJ100CA	100	111	123	1	5	162	30.9
5.0SMDJ110A	5.0SMDJ110CA	5.0SMDJ110A	5.0SMDJ110CA	110	122	135	1	5	177	28.3
5.0SMDJ120A	5.0SMDJ120CA	5.0SMDJ120A	5.0SMDJ120CA	120	133	147	1	5	193	26.0
5.0SMDJ130A	5.0SMDJ130CA	5.0SMDJ130A	5.0SMDJ130CA	130	144	159	1	5	209	24.0
5.0SMDJ150A	5.0SMDJ150CA	5.0SMDJ150A	5.0SMDJ150CA	150	167	185	1	5	243	20.6
5.0SMDJ160A	5.0SMDJ160CA	5.0SMDJ160A	5.0SMDJ160CA	160	178	197	1	5	259	19.3
5.0SMDJ170A	5.0SMDJ170CA	5.0SMDJ170A	5.0SMDJ170CA	170	189	209	1	5	275	18.2
5.0SMDJ180A	5.0SMDJ180CA	5.0SMDJ180A	5.0SMDJ180CA	180	201	222	1	5	292	17.5
5.0SMDJ190A	5.0SMDJ190CA	5.0SMDJ190A	5.0SMDJ190CA	190	211	233	1	5	308	16.5

Note:

1. Suffix "A" denotes 5% tolerance device.
2. Add suffix "CA" after part number to specify bi-directional devices.
3. The IR limit is double for bi-directional devices.



Rating and Characteristic Curves

FIG.1 - Peak Pulse Power Derating Curve




FIG.2 - Steady State Power Derating Curve




FIG.3 - Maximum Non-Repetitive Forward Surge Current Uni-Directional Only




FIG.4 - Pulse Waveform




FIG.5 - Typical Junction Capacitance





FIG.6 - Peak Pulse Power Rating Curve





Disclaimer

All specifications and data are subject to be changed without notice to improve reliability function or design or other reasons.

HY makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, HY disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on HY's knowledge of typical requirements that are often placed on HY products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify HY's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, HY products are not designed for use in medical, life-saving, or life-sustaining applications or for any other applications in which the failure of the HY product could result in personal injury or death. Customers using or selling HY products not expressly indicated for use in such applications do so at their own risk. Please contact authorized HY personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of HY. Product names and markings noted herein may be trademarks of their respective owners.