

SEMPER Gas Discharge Tube 230 V (for series 3402 platform 3000)

9071.99.0947

Properties

- Designed for operations exceeding 25 years
- GDT specification according to international standard ITU-T K.12
- Self Extinguisher GDT with holder included
- For EMP series 3402 platform 3000 operating up to 3GHz

**Interface and material data**

| | |
|----------------------------|-------------------------------|
| Housing material / plating | Brass / SUCOPLATE (R) Plating |
|----------------------------|-------------------------------|

Electrical data

| | |
|-----------------------------|--|
| CW power frame | ≤ 140 W |
| DC sparkover | 230 V, +/- 15 % (@ 100 V/s) |
| Impulse sparkover 100 V/μs | 450 V |
| Impulse sparkover 1000 V/μs | 675 V |
| Insulation resistance | > 10 GΩ (@ 100 V) |
| Glow voltage | approx. 70 V (@ 10 mA) |
| Arc voltage | approx. 10 V (@ > 1 A) |
| Glow-Arc transition current | < 0.5 A |
| Capacitance | < 1 pF (@ 1 MHz) |
| DC Holdover voltage | < 150 ms (@ 135 V) |
| Impulse discharge current | ≥ 1 operations (@ 30 kA, 8/20 μs) |
| | ≥ 10 operations (@ 20 kA, 8/20 μs) |
| | ≥ 400 operations (@ 500 A, 10/1000 μs) |
| | ≥ 1000 operations (@ 100 A, 10/1000 μs or 10/7000 μs) |
| Alter discharge current | ≥ 1 operations (@ 65 Arms, 11 cycles) |
| | ≥ 10 operations (@ 10 Arms, 1 s) |
| DC current | ≤ 2.5 A at 48 V |
| | ≤ 4 A at 27 V |
| | ≤ 6 A at 24 V |
| | ≤ 13 A at 17 V |
| Turn-off time | 20 sec. typically at 2.0 A and 25°C ambient temperature |
| | < 40 sec. typically below 1 A and 25°C ambient temperature |
| Recovery time | 7 sec. at 25°C ambient temperature |

SEMPER Gas Discharge Tube 230 V (for series 3402 platform 3000)

9071.99.0947

| Mechanical data | |
|------------------------|------|
| Weight | 14 g |

| Environmental data | |
|--------------------------------|---|
| Operation temperature | -20 °C ... 85 °C |
| Storage temperature | -40 °C ... 85 °C |
| Ingress protection (IP Rating) | Unmated / IP66, IP68, according to IEC 60529 (24 h of water, 1 m) |

| Additional Information | |
|-------------------------------|---|
| Remarks | GDT unit for retrofit and replacement for series 3402 (Platform 3000) |
| With capsule holder | Yes |

| Ordering Information Table | |
|-----------------------------------|------------------|
| Item number | Item description |
| 85031753 | 9071.99.0947 |

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P1210 / Date of publication: 01.03.2024 / uncontrolled copy