







		1	2	3	4	5	6	7																																																																						
A	 NOTE: 1.MATERIAL 1.1 Insulator:Nylon 66,UL94V-0,White 1.2 Contact:Brass,Tin over Nickel 2.ELECTRIC 2.1 Voltage Rating:250V AC/DC 2.2 Current Rating:3A AC/DC 2.3 Withstanding Voltage:800V AC/minute 2.4 Insulation Resistance:1000MΩ Min 3.Temperature Range:-40°C To +105°C 4.Packing:PE bag Order Code:A-WBP-L004EA-xxTB0x 3:Type 1 4:Type 2 No of contact <th>A</th>									A																																																																				
B										B																																																																				
C										C																																																																				
D										D																																																																				
E										E																																																																				
F										F																																																																				
	   <table><tr><th>Poles</th><th>③ Part No.</th><th colspan="2">Dimmensions (mm)</th></tr><tr><td></td><td></td><th>A</th><th>B</th></tr><tr><td>02</td><td>A-WBP-L004EA-02TB0x</td><td>2.50</td><td>7.50</td></tr><tr><td>03</td><td>A-WBP-L004EA-03TB0x</td><td>5.00</td><td>10.00</td></tr><tr><td>04</td><td>A-WBP-L004EA-04TB0x</td><td>7.50</td><td>12.50</td></tr><tr><td>05</td><td>A-WBP-L004EA-05TB0x</td><td>10.00</td><td>15.00</td></tr><tr><td>06</td><td>A-WBP-L004EA-06TB0x</td><td>12.50</td><td>17.50</td></tr><tr><td>07</td><td>A-WBP-L004EA-07TB0x</td><td>15.00</td><td>20.00</td></tr><tr><td>08</td><td>A-WBP-L004EA-08TB0x</td><td>17.50</td><td>22.50</td></tr><tr><td>09</td><td>A-WBP-L004EA-09TB0x</td><td>20.00</td><td>25.00</td></tr><tr><td>10</td><td>A-WBP-L004EA-10TB0x</td><td>22.50</td><td>27.50</td></tr><tr><td>11</td><td>A-WBP-L004EA-11TB0x</td><td>25.00</td><td>30.00</td></tr><tr><td>12</td><td>A-WBP-L004EA-12TB0x</td><td>27.50</td><td>32.50</td></tr><tr><td>13</td><td>A-WBP-L004EA-13TB0x</td><td>30.00</td><td>35.00</td></tr><tr><td>14</td><td>A-WBP-L004EA-14TB0x</td><td>32.50</td><td>37.50</td></tr><tr><td>15</td><td>A-WBP-L004EA-15TB0x</td><td>35.00</td><td>40.00</td></tr><tr><td>16</td><td>A-WBP-L004EA-16TB0x</td><td>37.50</td><td>42.50</td></tr></table> <th>D</th>	Poles	③ Part No.	Dimmensions (mm)				A	B	02	A-WBP-L004EA-02TB0x	2.50	7.50	03	A-WBP-L004EA-03TB0x	5.00	10.00	04	A-WBP-L004EA-04TB0x	7.50	12.50	05	A-WBP-L004EA-05TB0x	10.00	15.00	06	A-WBP-L004EA-06TB0x	12.50	17.50	07	A-WBP-L004EA-07TB0x	15.00	20.00	08	A-WBP-L004EA-08TB0x	17.50	22.50	09	A-WBP-L004EA-09TB0x	20.00	25.00	10	A-WBP-L004EA-10TB0x	22.50	27.50	11	A-WBP-L004EA-11TB0x	25.00	30.00	12	A-WBP-L004EA-12TB0x	27.50	32.50	13	A-WBP-L004EA-13TB0x	30.00	35.00	14	A-WBP-L004EA-14TB0x	32.50	37.50	15	A-WBP-L004EA-15TB0x	35.00	40.00	16	A-WBP-L004EA-16TB0x	37.50	42.50	D								
Poles	③ Part No.	Dimmensions (mm)																																																																												
		A	B																																																																											
02	A-WBP-L004EA-02TB0x	2.50	7.50																																																																											
03	A-WBP-L004EA-03TB0x	5.00	10.00																																																																											
04	A-WBP-L004EA-04TB0x	7.50	12.50																																																																											
05	A-WBP-L004EA-05TB0x	10.00	15.00																																																																											
06	A-WBP-L004EA-06TB0x	12.50	17.50																																																																											
07	A-WBP-L004EA-07TB0x	15.00	20.00																																																																											
08	A-WBP-L004EA-08TB0x	17.50	22.50																																																																											
09	A-WBP-L004EA-09TB0x	20.00	25.00																																																																											
10	A-WBP-L004EA-10TB0x	22.50	27.50																																																																											
11	A-WBP-L004EA-11TB0x	25.00	30.00																																																																											
12	A-WBP-L004EA-12TB0x	27.50	32.50																																																																											
13	A-WBP-L004EA-13TB0x	30.00	35.00																																																																											
14	A-WBP-L004EA-14TB0x	32.50	37.50																																																																											
15	A-WBP-L004EA-15TB0x	35.00	40.00																																																																											
16	A-WBP-L004EA-16TB0x	37.50	42.50																																																																											
G	RoHS compliant unit:mm  ② File No.: E198287 <table><tr><td>Scale</td><td>Free</td><td></td><td></td><td></td><td></td><td></td><td></td><td>Date</td><td>Name</td><td rowspan="4">Description: Wire to Board Wafer Pitch 2.50mm 90° THT ASSMANN WSW-NO. A-WBP-L004EA-xxTB0x</td></tr><tr><td colspan="2">TOLERANCE</td><td>④</td><td>Update the dimension of Cap</td><td>06.28.2024</td><td>Peter</td><td>Drawn</td><td>03.15.2022</td><td>Peter</td></tr><tr><td>X.</td><td>±0.35</td><td>③</td><td>Update WSW P/N (remove 17-20Pin)</td><td>01.25.2024</td><td>Peter</td><td>Approved</td><td>06.28.2024</td><td>Peter</td></tr><tr><td>X.X</td><td>±0.25</td><td>②</td><td>Add UL E-No. on page 1,3,4,5</td><td>03.16.2023</td><td>Peter</td><td></td><td></td><td></td></tr><tr><td rowspan="4">H</td><td>X.XX</td><td>±0.20</td><td>②</td><td>Add the page 6</td><td>09.23.2022</td><td>Winnie</td><td colspan="2" rowspan="4"></td><td>Drawing-No.</td><td rowspan="2">ASS 9266 CO</td><td rowspan="2">rev04</td></tr><tr><td>X.XXX</td><td>±0.15</td><td>①</td><td>Drawn</td><td>03.15.2022</td><td>Peter</td><td>Customer-No.</td><td>SHEET 2 / 8</td></tr><tr><td>DIM</td><td>TOL</td><td>①</td><td>Id.</td><td>modification</td><td>Date</td><td>Name</td><td></td><td></td></tr><tr><td>Angle</td><td>TOL</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>	Scale	Free							Date	Name	Description: Wire to Board Wafer Pitch 2.50mm 90° THT ASSMANN WSW-NO. A-WBP-L004EA-xxTB0x	TOLERANCE		④	Update the dimension of Cap	06.28.2024	Peter	Drawn	03.15.2022	Peter	X.	±0.35	③	Update WSW P/N (remove 17-20Pin)	01.25.2024	Peter	Approved	06.28.2024	Peter	X.X	±0.25	②	Add UL E-No. on page 1,3,4,5	03.16.2023	Peter				H	X.XX	±0.20	②	Add the page 6	09.23.2022	Winnie			Drawing-No.	ASS 9266 CO	rev04	X.XXX	±0.15	①	Drawn	03.15.2022	Peter	Customer-No.	SHEET 2 / 8	DIM	TOL	①	Id.	modification	Date	Name			Angle	TOL								G
Scale	Free							Date	Name	Description: Wire to Board Wafer Pitch 2.50mm 90° THT ASSMANN WSW-NO. A-WBP-L004EA-xxTB0x																																																																				
TOLERANCE		④	Update the dimension of Cap	06.28.2024	Peter	Drawn	03.15.2022	Peter																																																																						
X.	±0.35	③	Update WSW P/N (remove 17-20Pin)	01.25.2024	Peter	Approved	06.28.2024	Peter																																																																						
X.X	±0.25	②	Add UL E-No. on page 1,3,4,5	03.16.2023	Peter																																																																									
H	X.XX	±0.20	②	Add the page 6	09.23.2022	Winnie			Drawing-No.	ASS 9266 CO	rev04																																																																			
	X.XXX	±0.15	①	Drawn	03.15.2022	Peter			Customer-No.			SHEET 2 / 8																																																																		
	DIM	TOL	①	Id.	modification	Date			Name																																																																					
	Angle	TOL																																																																												
	1	2	3	4	5	6	7																																																																							

	1	2	3	4	5	6	7																																																																															
A	2.50±0.10 A±0.20 PCB LAYOUT NOTE: 1.MATERIAL 1.1 Insulator:Nylon 66,UL94V-0,White 1.2 Contact:Brass,Tin over Nickel 2.ELECTRIC 2.1 Voltage Rating:250V AC/DC 2.2 Current Rating:3A AC/DC 2.3 Withstanding Voltage:800V AC/minute 2.4 Insulation Resistance:1000MΩ Min 3.Temperature Range:-40°C To +105°C 4.Packing:PE bag Order Code:A-WBP-L004EG-xxTB0x 1:Type 1 2:Type 2 3:Type 3							A																																																																														
B								B																																																																														
C								C																																																																														
D								D																																																																														
E								E																																																																														
F								F																																																																														
G	RoHS compliant unit:mm ② File No.: E198287		<table><tr><td>Scale</td><td>Free</td><td></td><td></td><td></td><td></td><td></td><td>Date</td><td>Name</td><td colspan="2">Description: Wire to Board Wafer Pitch 2.50mm 180° THT</td></tr><tr><td colspan="2">TOLERANCE</td><td>④</td><td>Update the dimension of Cap</td><td>06.28.2024</td><td>Peter</td><td>Drawn</td><td>03.15.2022</td><td>Peter</td><td colspan="2" rowspan="3">ASSMANN WSW-NO. A-WBP-L004EG-xxTB0x</td></tr><tr><td>X.</td><td>±0.35</td><td>③</td><td>Update WSW P/N (remove 17-20Pin)</td><td>01.25.2024</td><td>Peter</td><td>Approved</td><td>06.28.2024</td><td>Peter</td></tr><tr><td>X.X</td><td>±0.25</td><td>②</td><td>Add UL E-No. on page 1,3,4,5</td><td>03.16.2023</td><td>Peter</td><td></td><td></td><td></td></tr><tr><td>X.XX</td><td>±0.20</td><td>①</td><td>Add the page 6</td><td>09.23.2022</td><td>Winnie</td><td colspan="3" rowspan="3"></td><td>Drawing-No.</td><td rowspan="2">ASS 9266 CO</td><td rowspan="2">rev04</td></tr><tr><td>X.XXX</td><td>±0.15</td><td>①</td><td>Drawn</td><td>03.15.2022</td><td>Peter</td><td>Customer-No.</td><td>SHEET 3 / 8</td></tr><tr><td>DIM</td><td>TOL</td><td>①</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>Angle</td><td>TOL</td><td>Id.</td><td>modification</td><td>Date</td><td>Name</td><td colspan="3"></td><td></td><td></td></tr></table>	Scale	Free						Date	Name	Description: Wire to Board Wafer Pitch 2.50mm 180° THT		TOLERANCE		④	Update the dimension of Cap	06.28.2024	Peter	Drawn	03.15.2022	Peter	ASSMANN WSW-NO. A-WBP-L004EG-xxTB0x		X.	±0.35	③	Update WSW P/N (remove 17-20Pin)	01.25.2024	Peter	Approved	06.28.2024	Peter	X.X	±0.25	②	Add UL E-No. on page 1,3,4,5	03.16.2023	Peter				X.XX	±0.20	①	Add the page 6	09.23.2022	Winnie				Drawing-No.	ASS 9266 CO	rev04	X.XXX	±0.15	①	Drawn	03.15.2022	Peter	Customer-No.	SHEET 3 / 8	DIM	TOL	①									Angle	TOL	Id.	modification	Date	Name						G
Scale			Free						Date	Name	Description: Wire to Board Wafer Pitch 2.50mm 180° THT																																																																											
TOLERANCE			④	Update the dimension of Cap	06.28.2024	Peter	Drawn	03.15.2022	Peter	ASSMANN WSW-NO. A-WBP-L004EG-xxTB0x																																																																												
X.			±0.35	③	Update WSW P/N (remove 17-20Pin)	01.25.2024	Peter	Approved	06.28.2024			Peter																																																																										
X.X			±0.25	②	Add UL E-No. on page 1,3,4,5	03.16.2023	Peter																																																																															
X.XX			±0.20	①	Add the page 6	09.23.2022	Winnie				Drawing-No.	ASS 9266 CO	rev04																																																																									
X.XXX			±0.15	①	Drawn	03.15.2022	Peter				Customer-No.			SHEET 3 / 8																																																																								
DIM			TOL	①																																																																																		
Angle			TOL	Id.	modification	Date	Name																																																																															
H	H																																																																																					
	1	2	3	4	5	6	7																																																																															

		1	2	3	4	5	6	7		
A										

