



AC38S-Q

600V • 2 Form A

AEC-Q101
Certification



RoHS compliant

Features

- Contact Form 2a
- Load Voltage 600 V Max.
- Operation LED Current 3mA Max.
- Load Current 70mA Max.
- On-Resistance 40Ω Typ.
- Output Capacitance 47 pF Typ.

Application:



- Automobile BMS Controller
- Energy Storage System Big-
- data storage

Part Identification

SOP Type		Quantity
Stick	Tape & Reel	Stick 50
	Feed direction : Pin No. 5,6,7,8	
AC38S-Q		Tape 1000

Terminal Identification 電路結構圖

Terminal Identification



- 1,3: Anode (LED)
2,4: Cathode (LED)
5,6,7,8: Drain (MOS FET)

* Recommended Soldering Pattern
For Reflow Soldering

Absolute Maximum Ratings 絶對最大定格 (Ambient Temperature 周圍溫度 : 25°C)

Item		Symbol	Value
Input 輸入	Continuous LED Current 連續的LED電流	I _F	50mA
	Peak LED Current LED的峰值電流 (f=100 Hz duty=1%)	I _{FP}	500mA
	LED Reverse Voltage 逆向的LED電壓	V _R	5V
	Input Power Dissipation 容許損失	P _{In}	75mW
Output 輸出	Load Voltage 負荷電壓	V _L	600V(AC peak or DC)
	Load Current 負荷電流	I _L	70mA(1ch) 60mA(2ch)
	Peak Load Current 峰值負荷電流(1 ms,1 shot)	I _{Peak}	200mA
	Output Power Dissipation 電流損耗	P _{Out}	300mW(1ch) 450mW(2ch)
Total Power Dissipation 全損耗		P _T	350mW(1ch) 500mW(2ch)
I/O Breakdown Voltage 入/出力間絕緣電壓		V _{I/O}	1500Vrms Min.
Operating Temperature 使用時周圍溫度 *		T _{Op}	-40°C ~ +105°C
Storage Temperature 周圍保存溫度 *		T _{Stg}	-40°C ~ +125°C

* The temperature is based on AEC-Q101 certification.

Recommended Operating Condition 建議使用條件 (Ambient Temperature 周圍溫度: 25 °C)

Item	Symbol	Number of used channels	MIN.	TYP.	MAX.	units
Continuous LED Current 連續的 LED 電流	I _F		5	10	15	mA
Load Voltage 負荷電壓	V _L		---	---	300	V
Load Current 負荷電流	I _L	1 ch	---	---	35	mA
		2 ch			30	

Electrical Specifications LED順向電壓(Ambient Temperature 周圍溫度 : 25°C)

Item		Symbol	MIN.	TYP.	MAX.	Units	Conditions
Input 輸入	LED Forward Voltage LED順向電壓	V _F	0.9	1.17	1.3	V	I _F =10mA
	Operation LED Current LED的動作電流	I _{F On}		0.5	3	mA	
	Recovery LED Voltage LED的恢復電壓	V _{F Off}	0.5	1		V	
Output 輸出	On-Resistance 導通電阻 Drain to Drain	R _{On}		40	60	Ω	I _F =5mA, I _L = Rated Current Time to flow is within 1sec.
	Off-State Leakage Current 開路狀態時的電流	I _{Leak}			1	uA	V _L = 600V
	Output Capacitance 輸出端容量	C _{Out}		47		pF	V _L =0V, f=1MHz
Transmission 傳達	Turn-On Time 動作時間	T _{On}		0.1	0.5	ms	I _F =5mA I _L =Rated Current
	Turn-Off Time 復位時間	T _{Off}		0.15	0.5	ms	
Coupled 結合	I/O Insulation Resistance 輸入/出間的絕緣阻抗	R _{I/O}	10 ⁹			Ω	
	I/O Capacitance 輸入/力端的靜電容量	C _{I/O}		1.3		pF	f=1MHz

