



Highlights

2 to 12 poles

2 and 3 pole modules

Spacing 7.5 mm

Wire guard type

Wire entry parallel to PCB

Test jack on every clamping point

24 A with 2.5 mm² wire

Wire Sizes

Solid min 0.2 mm²

Solid max 2.5 mm²

Stranded (flexible) min 0.2 mm²

Stranded (flexible) max 2.5 mm²

Stranded with ferrule min 0.2 mm²

Stranded with ferrule max 2.5 mm²

Dimensions

Stripped length 7.0 mm

PCB hole diameter 1.3 mm

Materials

Clamp Brass

Wire guard Stainless Steel

Screw Steel

Insulating Material

Material PA 6.6

Flammability class UL 94 V-0

Temperatures

Operating temperature -40 °C (without mech. load) - 105 °C

Store temperature -40 °C - 105 °C

Spacing 7.5 mm

Wave Soldering Process

Soldering temperature, recommended	260 °C
Peak soldering time, recommended	3-4 s

Reflow Process

Soldering temperature, recommended	-
Peak soldering time, recommended	-

Colours

GREY, RAL 7016

BLACK, RAL 9011

RED, RAL 3003

LIGHT GREEN, similar RAL 6018

Colours according to RAL, there may be variations on colour due to production conditions.
 Special colours on request.

Ratings

					
UseGroup	B	C	D		
Rated voltage	300 V	150 V	300 V		750 V
Rated current	20 A	20 A	10 A		24 A
Rated wire size				min	max
- solid	AWG 22-14	AWG 22-14	AWG 22-14	0.5 mm ²	2.5 mm ²
- stranded	-	-	-	-	-
- stranded (flexible)	AWG 22-14	AWG 22-14	AWG 22-14	0.5 mm ²	2.5 mm ²
Torque	0.45 Nm	0.45 Nm	0.45 Nm		0.50 Nm
Screw size	M3	M3	M3		M3
Test voltage	1.60 kV	1.30 kV	1.60 kV		3.0 kV

Accessoires

Figure	Designation	Article Number
	Bridge, 2-pole, insulated, BRI/2-7.5/7.62-L8.2-LIGHT GREY	Art.-Nr. 50000000017



Technical Data // AK110/..DS-7.5-V-GREY

PTR HARTMANN

A Phoenix Mecano Company

Spacing 7.5 mm

Order Data (Spacing 7.5 mm)

Number of Poles	Width (mm)	Article Designation	Article Number	PU
2	15.70	AK110/2DS-7.5-V-GREY	50110020070 F	200
3	23.20	AK110/3DS-7.5-V-GREY	50110030070 F	200
4	30.70	AK110/4DS-7.5-V-GREY	50110040070 F	200
5	38.20	AK110/5DS-7.5-V-GREY	50110050070 E	100
6	45.70	AK110/6DS-7.5-V-GREY	50110060070 E	100
7	53.20	AK110/7DS-7.5-V-GREY	50110070070 E	100
8	60.70	AK110/8DS-7.5-V-GREY	50110080070 E	100
9	68.20	AK110/9DS-7.5-V-GREY	50110090070 E	100
10	75.70	AK110/10DS-7.5-V-GREY	50110100070 D	50
11	83.20	AK110/11DS-7.5-V-GREY	50110110070 D	50
12	90.70	AK110/12DS-7.5-V-GREY	50110120070 D	50

Technical drawing

