



Highlights

2 to 12 poles

Spacing 7.5 mm

Lift type

Wire entry parallel to PCB

24 A with 2.5 mm² wire

Wire Sizes

Solid min	0.2 mm ²
-----------	---------------------

Solid max	4.0 mm ²
-----------	---------------------

Stranded (flexible) min	0.2 mm ²
-------------------------	---------------------

Stranded (flexible) max	2.5 mm ²
-------------------------	---------------------

Stranded with ferrule min	0.25 mm ²
---------------------------	----------------------

Stranded with ferrule max	2.5 mm ²
---------------------------	---------------------

Dimensions

Stripped length	8.0 mm
-----------------	--------

PCB hole diameter	1.3 mm
-------------------	--------

Materials

Clamp	Brass
-------	-------

Screw	Steel
-------	-------

Solder tab	Copper Alloy
------------	--------------

Insulating Material

Material	PA 6.6
----------	--------

Flammability class	UL 94 V-0
--------------------	-----------

Temperatures

Operating temperature	-40 °C (without mech. load) - 105 °C
-----------------------	--------------------------------------

Store temperature	-40 °C - 105 °C
-------------------	-----------------

Wave Soldering Process

Soldering temperature, recommended	260 °C
------------------------------------	--------

Peak soldering time, recommended	3-4 s
----------------------------------	-------

Spacing 7.5 mm

Reflow Process

Soldering temperature, recommended	-
Peak soldering time, recommended	-

Colours

GREEN, RAL 6018

BLACK, RAL 9011

PEBBLE GREY, RAL 7032

BLUE, RAL 5015

LIGHT GREEN, similar RAL 6018

Colours according to RAL, there may be variations on colour due to production conditions.
Special colours on request.

Ratings

					
UseGroup	B	C	D		
Rated voltage	300 V	150 V	300 V		750 V
Rated current	20 A	20 A	10 A		24 A
Rated wire size				min	max
- solid	AWG 30-12	AWG 30-12	AWG 30-12	0.5 mm ²	4.0 mm ²
- stranded	-	-	-	-	-
- stranded (flexible)	AWG 30-12	AWG 30-12	AWG 30-12	0.5 mm ²	2.5 mm ²
Torque	0.45 Nm	0.45 Nm	0.45 Nm		0.50 Nm
Screw size	M3	M3	M3		M3
Test voltage	1.60 kV	1.30 kV	1.60 kV		3.0 kV

Accessoires

Figure	Designation	Article Number
	Bridge, 2-pole, insulated, BRI/2-7.5/7.62-L8.2-LIGHT GREY	Art.-Nr. 50000000017
	Screw Cover SC-AK700-YELLOW	Art.-Nr. 50700000004



PTR HARTMANN

A Phoenix Mecano Company

Technical Data // AK710/..-7.5-V-GREEN

Spacing 7.5 mm

Order Data (Spacing 7.5 mm)

Number of Poles	Width (mm)	Article Designation	Article Number	PU
2	15.60	AK710/2-7.5-V-GREEN	50710020201 E	100
3	23.10	AK710/3-7.5-V-GREEN	50710030201 E	100
4	30.60	AK710/4-7.5-V-GREEN	50710040201 E	100
5	38.10	AK710/5-7.5-V-GREEN	50710050201 E	100
6	45.60	AK710/6-7.5-V-GREEN	50710060201 D	50
7	53.10	AK710/7-7.5-V-GREEN	50710070201 D	50
8	60.60	AK710/8-7.5-V-GREEN	50710080201 D	50
9	68.10	AK710/9-7.5-V-GREEN	50710090201 D	50
10	75.60	AK710/10-7.5-V-GREEN	50710100201 D	50
11	83.10	AK710/11-7.5-V-GREEN	50710110201 D	50
12	90.60	AK710/12-7.5-V-GREEN	50710120201 D	50

Technical drawing

