



Highlights

- 2 to 20 poles
- Push-In connection
- Spacing 3.81 mm
- Wire entry parallel to plugging direction
- Coding with coding nose
- Lever for easy opening of clamping point
- Test jack on every clamping point

Wire Sizes

Solid min	0.14 mm ²
Solid max	1.5 mm ²
Stranded (flexible) min	0.14 mm ²
Stranded (flexible) max	1.5 mm ²
Stranded with ferrule min	0.25 mm ²
Stranded with ferrule max	1.0 mm ²

Dimensions

Stripped length	9.0 ... 10.0 mm
-----------------	-----------------

Materials

Contact spring	Copper Alloy
Clamp spring	Stainless Steel

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-0

Temperatures

Operating temperature	-40 °C (without mech. load) - 105 °C
Store temperature	-40 °C - 105 °C

Wave Soldering Process

Soldering temperature, recommended	-
Peak soldering time, recommended	-

Spacing 3.81 mm

Reflow Process

Soldering temperature, recommended -

Peak soldering time, recommended -

Colours

BASALT GREY, RAL 7012

GREEN, RAL 6018

LIGHT GREEN, similar RAL 6018

Colours according to RAL, there may be variations on colour due to production conditions.
Special colours on request.

Ratings

					
UseGroup	B	C	D		
Rated voltage	300 V	-	300 V	160 V	
Rated current	10 A	-	10 A	10 A	
Overvoltage category				III	
Rated wire size				min	max
- solid	AWG 26-16	-	AWG 26-16	0.14 mm ² (3 A)	2.5 mm ² (10 A)
- stranded	-	-	-	-	-
- stranded (flexible)	AWG 26-16	-	AWG 26-16	0.14 mm ² (3 A)	1.5 mm ² (10 A)
Test voltage	1.60 kV	-	1.60 kV	2.5 kV	
Pollution degree				3	

Counterparts (Spacing 3.81 mm)

Pin Strip

STLZ1550 STLZ1570 STLZ1590

In combination of connectors with different admission data, the lower value is valid.

Accessoires

Figure	Designation	Article Number
	Series AK(Z)4551 with pull relief	Art.-Nr. on request



Technical Data // AKZ4551/..KD-3.81-BASALTGREY

PTR HARTMANN

A Phoenix Mecano Company

Spacing 3.81 mm

Order Data (Spacing 3.81 mm)

Number of Poles	Width (mm)	Article Designation	Article Number	PU
2	7.62	AKZ4551/2KD-3.81-BASALTGREY	54551020421 F	200
3	11.43	AKZ4551/3KD-3.81-BASALTGREY	54551030421 F	200
4	15.24	AKZ4551/4KD-3.81-BASALTGREY	54551040421 F	200
5	19.05	AKZ4551/5KD-3.81-BASALTGREY	54551050421 F	200
6	22.86	AKZ4551/6KD-3.81-BASALTGREY	54551060421 E	100
7	26.67	AKZ4551/7KD-3.81-BASALTGREY	54551070421 E	100
8	30.48	AKZ4551/8KD-3.81-BASALTGREY	54551080421 D	50
9	34.29	AKZ4551/9KD-3.81-BASALTGREY	54551090421 D	50
10	38.10	AKZ4551/10KD-3.81-BASALTGREY	54551100421 D	50
11	41.91	AKZ4551/11KD-3.81-BASALTGREY	54551110421 D	50
12	45.72	AKZ4551/12KD-3.81-BASALTGREY	54551120421 D	50
13	49.53	AKZ4551/13KD-3.81-BASALTGREY	54551130421 D	50
14	53.34	AKZ4551/14KD-3.81-BASALTGREY	54551140421 D	50
15	57.15	AKZ4551/15KD-3.81-BASALTGREY	54551150421 D	50
16	60.96	AKZ4551/16KD-3.81-BASALTGREY	54551160421 D	50
17	64.77	AKZ4551/17KD-3.81-BASALTGREY	54551170421 D	50
18	68.58	AKZ4551/18KD-3.81-BASALTGREY	54551180421 D	50
19	72.39	AKZ4551/19KD-3.81-BASALTGREY	54551190421 D	50
20	76.20	AKZ4551/20KD-3.81-BASALTGREY	54551200421 D	50

Technical drawing

