




| REVISIONS | | | | | | |
|-----------|-----|------------------------|-----------|--------|-------|--|
| REV | ECO | DESCRIPTION | DATE | BY | APPR | |
| A3 | - | RELEASE NEW DWG FORMAT | 21/JUL/14 | JARRY | - | |
| A3N | - | ADD RATED VOLTAGE | 18/DEC/17 | ORION | TOMMY | |
| A4 | - | UPDATE SHAPE OF LATCH | 07/OCT/20 | SULLEN | TOMMY | |







NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:

HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER

- 2. MODIFICATIONS: REDUCED DIAMETER SEAL WITH END CAP
- 3. SPECIFICATIONS:
 - 3.1 CURRENT RATING: 25 AMPS
 - 3.2 VOLTAGE RATING: 500 V AC/DC (UL1977)
 - 3.3 OPERATING TEMPERATURE: -55°C TO +125°C
 - 3.4 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 2500 VOLTS AC. 3.5 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.

 - 3.6 MOISTURE RESISTANCE:

IP68(1M OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION) IP69K(MATED CONDITION)

(.158 in) (3.0-2.0mm²)

- 3.7 MATING CYCLE DURABILITY: 100 CYCLES
- 3.8 ROHS COMPLIANT
- 4. MATING PART: ATP04-4P* RECEPTACLE. (* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

| <u>/6</u> \ | 6 CONTACT SIZE AND REAR SEAL WIRE RANGE: | | | | | | | |
|-------------|--|------------|------------|-------------|--|--|--|--|
| | CONTACT | MIN. INSUL | MAX. INSUL | TYPICAL | | | | |
| | SIZE | O.D. | O.D. | WIRE RANGI | | | | |
| | | 2 46 mm | 4 01 mm | 12 - 14 AWG | | | | |

(.097 in)

| PART N | JMBER CHART | |
|--------|-----------------|--|
| COLOR | PART NUMBER | |
| GREY | ATP06-4S-MM01 | |
| BLACK | ATP06-4S-MM01BK | |

STANDARD MOLDED COLOR IS GREY. ADDITIONAL COLOR (BLACK) IS AVAILABLE VIA SPECIAL ORDER.

AMPHENOL

25.5

| | SEE PART N | UMBER (| CHART | | | | | |
|--|-------------------------------|--|----------------|---|--------------------------------------|------|----------------------------|----|
| | PART N | IUMBEF | ₹ | | DESCRIPTION ITEM | | | |
| QUANTITY MATER | | | | | ALS | S LI | ST | |
| | WISE SPECIFIED | SIGI | NATURE | S DATE | | Λ | mahanal | |
| All dimensions are in metric(mm). Tolerances are as follows: | | DRAWN: | SULLEN.ZHANG | 9 07/OCT/20 | | | mphenol | |
| 1 PL DEC ±0.30 2 PL DEC ±0.15 3 PL DEC ±0.08 | Fractions ±1/64 Angles ±1° | CHECKED: | ORION.LI | 08/OCT/20 | Sine Systems - www.amphenol-sine.com | | | |
| 3) Note reference = X | | ENGINEER: | | | 44724 Morley Drive | | | |
| MATERIAL SPECIFICA | TIONS | APPROVAL: | TOMMY.XIE | 09/OCT/20 | | | Clinton Township, MI 48036 | |
| MATERIAL OF EOU TO | ilono. | CUSTOMER: | | | | | S, PLUG, SOCKET, REDUCED | |
| | | | NG IS SUPPLIED | | DI | AMET | ER SEAL, END CAP, ATP SERI | ES |
| PROCESS SPECIFICATIONS: | | SPECIFICATI SHOWN HER THE AMPHEN OF REPRODI | EON ARE THE | FORMANCE DATA PROPERTY OF FION. NO RIGHTS PLIED. ALL | B | C- | ATP06-4S-MM01XX | A4 |
| NEXT ASS'Y: | | | IRING VARIATIO | | SCALE: N | ONE | SHEET 1 OF | 1 |

TITLE: 4 POS, PLUG, SOCKET, REDUCED DIAMETER SEAL, END CAP, ATP SERIES

ATP06-4S-MM01XX REV: A4

A Series™ - Contact Size 12 Options (Works with: AHD-6, ATP, ATHD, DuraMate and PanelMate Series)

| Machined Contacts, Sockets & Pins | | | | |
|-----------------------------------|--|------|-------|----------|
| Part Number | Description | Size | AWG | Туре |
| *AT60-204-12141-10 | Male Contact - Pin, Nickel-plated | 12 | 10-12 | Machined |
| *AT62-203-12141-10 | Female Contact - Socket, Nickel-plated | 12 | 10-12 | Machined |
| AT60-220-1231 | Male Contact - Pin, Gold-plated | 12 | 12-14 | Machined |
| AT62-210-1231 | Female Contact - Socket, Gold-plated | 12 | 12-14 | Machined |
| AT60-204-12141 | Male Contact - Pin, Nickel-plated | 12 | 12-14 | Machined |
| AT62-203-12141 | Female Contact - Socket, Nickel-plated | 12 | 12-14 | Machined |

^{*}Works with ATP Series only

| | DiagnosticGrade™ Machined Contacts, Sockets & Pins • Smaller AWG for Diagnostic Applications • Gold-plated • Increased Mating Cycles • Cost-effective | | | | |
|-------------------------|--|---|------|-----|----------|
| Part Number Description | | Description | Size | AWG | Туре |
| Γ | 65-54749 | Male Contact - DiagnosticGrade™, Pin, Gold-plated | 12 | 20 | Machined |
| | AT62-210-1231-1820 | Female Contact - DiagnosticGrade™, Socket, Gold-plated | 12 | 20 | Machined |

| | Tooling - Machined Contacts | | | |
|-------------------------|--|--|--|--|
| Part Number Description | | | | |
| AUTK-12 | Hand Crimp Tool, Size 12 | | | |
| AUTK-100 | Universal Heavy Duty Contact Crimping Tool Kit, Size 12/16/20 | | | |
| CA-5D12 | Universal Hand Crimp Tool, Size 12/16/20 | | | |
| CA-5E12 | Pneumatic Crimp Tool, Size 12/16/20 | | | |
| M300-25A | Hand Crimp Tool used with Crimp Locator MFX-3966, Size 12, 10AWG | | | |
| MFX-3966 | Contact Locator used with Hand Crimp Tool M300-25A, Size 12, 10AWG | | | |

| Contact Removal Tools (For both Machined or Stamped & Formed Contacts) | | | | |
|--|--|--|--|--|
| Part Number | Description | | | |
| ATRT-100 | Contact and Wedgelock Extraction Tool | | | |
| AT11-337-1205 | Contact Removal Tool, Plastic, Size 12 | | | |

| Sealing Plugs (For both Machined or Stamped & Formed Contacts) | | | |
|--|------------------------------|--|--|
| Part Number | Description | | |
| A114017 | Sealing Plug, Size 12, White | | |

| Stamped & Formed Contacts, Sockets & Pins | | | | | |
|---|--|------|-------|------------------|--|
| Part Number | Description | Size | AWG | Туре | |
| AT60-12-0244 | Male Contact - Pin, Gold-plated | 12 | 10-12 | Stamped & Formed | |
| AT62-12-0244 | Female Contact - Socket, Gold-plated | 12 | 10-12 | Stamped & Formed | |
| AT60-12-0222 | Male Contact - Pin, Nickel-plated | 12 | 10-12 | Stamped & Formed | |
| AT62-12-0222 | Female Contact - Socket, Nickel-plated | 12 | 10-12 | Stamped & Formed | |
| AT60-12-0144 | Male Contact - Pin, Gold-plated | 12 | 12-14 | Stamped & Formed | |
| AT62-12-0144 | Female Contact - Socket, Gold-plated | 12 | 12-14 | Stamped & Formed | |
| AT60-12-0166 | Male Contact - Pin, Nickel-plated | 12 | 12-14 | Stamped & Formed | |
| AT62-12-0166 | Female Contact - Socket, Nickel-plated | 12 | 12-14 | Stamped & Formed | |

| Tooling - Stamped & Formed Contacts | | | | |
|--|----------------------------------|--|--|--|
| Part Number Description | | | | |
| MFX-3973 | Crimp Die - Size 12 | | | |
| MFX-3985 Crimp Die - Svize 12, 10-12AWG -02XX Series | | | | |
| ATT-12-00 | Hand Crimp Tool - Size 12, 12AWG | | | |
| ATT-12-01 | Hand Crimp Tool - Size 12, 10AWG | | | |