

FEATURES



- Low leakage current, long life
- High Temperature
- Small size and low-resistance
- Temperature 85°C/85% Humidity
- REACH,RoHS Directive Compliant

APPLICATIONS

- Scanners,Medical equipment,Main power ,Back up power , UPS/Industrial ,Wireless Alarms,Water and gas smart meters.



OPERATING TEMPERATURE RANGE

- -40°C to +85°C @5.5V Balanced, 5.0V Unbalanced


GENERAL SPECIFICATIONS

Item	Performance
Operating temperature	-40°C to +85°C
Capacitance range	0.1F to 50F
Rated voltage	5.5 V
Surge voltage	5.7 V
Temperature characteristics	Capacitance change: Within ±30% of initial measured value at +25°C Internal resistance: Within ±200% of initial measured value at +25°C
High temperature load time	After 85°C 1000 hours H:85% (at 5.0V) Capacitance change: ±30% of initial rated value Internal resistance: Within 3 times of initial specified value
Projected cycle life (From rated voltage to 1/2 rated voltage at 25°C)	After 500,000 cycles: Capacitance change: Within ±30 % of initial rated value Internal resistance: Within 2 times of initial specified value
Humidity characteristic	Relative humidity: 90%~95% /Duration of testing:240 hrs /Temperature:40±2°C Capacitance change: Within ±30 % of initial rated value Internal resistance: Within 2 times of initial specified value
Vibration resistance	Amplitude:1.5mm /Frequency:10~55Hz /Duration: X,Y,Z(2 hrs)/Duration of testing:6 hrs Capacitance change: Within ±30 % of initial rated value Internal resistance: Within 2 times of initial specified value
Shelf life	After 2 years at 25°C without load, the capacitor shall meet the specified endurance limits.

PART NUMBER SYSTEM

CHT	5R5	L	105	R	TW	*	**
Series	Rated Voltage	Connection Code	Capacity Code	Environmental Code	MFG Code	Special Code	PIN Code


Casing Display:



DIMENSIONS




DA Type




D	P(mm)	Φd
4	5.8	0.5
5	7.5	0.5
7	10.0	0.6
8	11.5	0.6
10	15.5	0.6
13	17.5	0.6
16	23.7	0.8
18	26.0	0.8

DB Type




D	P(mm)	Φd
4	2.5	0.5
5	3.5	0.5
7	5.0	0.6
8	5.0	0.6
10	5.5	0.6
13	7.5	0.6
16	8.5	0.8
18	10.5	0.8

DC Type



D	P(mm)	Φd
4	/	0.5
5	/	0.5
7	/	0.6
8	8.0	0.6
10	10.0	0.6
13	13.0	0.6
16	16.0	0.8
18	20.0	0.8


DZ Type




D	P(mm)	B(mm)	Φd
4	5.8	2.0	0.5
5	7.5	2.0	0.5
7	10.0	2.0	0.6
8	11.5	2.0	0.6
10	15.5	2.0	0.6
13	17.5	2.0	0.6
16	23.7	2.0	0.8
18	26.0	2.0	0.8

*for version with bent leads

CL Type



CA Type



*Connectors can be customized




STANDARD PRODUCTS



Part Number	Rated Voltage (V)	Rated Cap (F)	Capacitance Tolerance	Size(mm)			Max.ESR		Maximum Endurance Current(A)	Maximum Peak Current(A)	Maximum Leakage Current (72hrs/mA)	Power Density (W/Kg)	Maximum Energy (W.h)	Energy Density (Wh/kg)
				W	D	L	ESRAC (1kHz/mΩ)	ESRDC (mΩ)						
5.4V Series-Connected SuperCapacitors Modules(Miniaturized)														
*CHT-5R4L104R-TW	5.4	0.1	-10%~+30%	10	5	12	1400	6000	0.09	0.18	0.002	729	0.0004	0.50
*CHT-5R4L224R-TW	5.4	0.22	-10%~+30%	10	5	14	1100	3500	0.13	0.36	0.002	1075	0.0009	0.95
*CHT-5R4L504R-TWX	5.4	0.5	-10%~+30%	13	7	14	400	2000	0.18	0.61	0.003	1094	0.0020	1.26
*CHT-5R4L474R-TWX	5.4	0.47	-10%~+30%	13	7	14	400	2000	0.18	0.61	0.003	1094	0.0019	1.19
5.5V Series-Connected SuperCapacitors Modules(Miniaturized)														
*CHT-5R5L104R-TW	5.5	0.1	-0%~+100%	10	5	12	900	1800	0.09	0.17	0.001	660	0.00042	0.38
*CHT-5R5L124R-TW	5.5	0.12	-0%~+100%	9	4	12	2000	3600	0.09	0.17	0.001	693	0.00050	0.38
*CHT-5R5L224R-TWX	5.5	0.22	-0%~+100%	10	5	14	800	1500	0.12	0.42	0.002	1117	0.00092	0.92
*CHT-5R5L224R-TW	5.5	0.22	-0%~+100%	13	7	14	400	800	0.14	0.60	0.006	3025	0.00092	1.00
*CHT-5R5L474R-TWQ	5.5	0.47	-0%~+100%	9	4	27	1100	1800	0.18	0.54	0.003	2046	0.0019	1.78
*CHT-5R5L504R-TWX	5.5	0.5	-0%~+100%	13	7	14	400	1000	0.16	0.66	0.006	2499	0.0020	1.36
*CHT-5R5L155R-TWQ	5.5	1.5	-0%~+100%	13	7	24	190	380	0.53	2.71	0.010	2880	0.0070	3.00
*CHT-5R5L205R-TW	5.5	2.0	-0%~+100%	13	7	27	190	380	0.56	3.00	0.010	2400	0.0090	3.33
5.4V Series-Connected SuperCapacitors Modules														
CHT-5R4L504R-TW	5.4	0.5	-10%~+30%	16	8	14	320	480	0.50	1.08	0.006	3240.00	0.0020	0.90
CHT-5R4L474R-TW	5.4	0.47	-10%~+30%	16	8	14	320	480	0.47	1.05	0.006	3240.00	0.0019	0.85
CHT-5R4L105R-TW	5.4	1.0	-10%~+30%	16	8	18	240	360	0.61	2.02	0.010	3640.45	0.0041	1.52
CHT-5R4L155R-TW	5.4	1.5	-10%~+30%	16	8	22	200	300	0.74	2.84	0.012	3645.00	0.0061	1.89
CHT-5R4L255R-TWV	5.4	2.5	-10%~+30%	16	8	27	180	270	0.87	4.10	0.015	3049.41	0.0101	2.38
CHT-5R4L255R-TW	5.4	2.5	-10%~+30%	20	10	22	150	225	0.97	4.40	0.015	2996.53	0.0101	1.95
*CHT-5R4L305R-TW	5.4	3.0	-10%~+30%	16	8	32	120	200	1.16	7.11	0.028	3630.00	0.0126	4.20
CHT-5R4L355R-TW	5.4	3.5	-10%~+30%	20	10	22	120	180	1.20	5.90	0.018	3633.64	0.0142	2.64
*CHT-5R4L355R-TWV	5.4	3.5	-10%~+30%	16	8	27	170	370	0.75	4.18	0.018	2102.00	0.0142	3.15
CHT-5R4L505R-TW	5.4	5.0	-10%~+30%	20	10	27	120	180	1.20	7.24	0.030	3278.25	0.0203	3.41
CHT-5R4L505R-TWQ	5.4	5.0	-10%~+30%	20	10	32	90	150	1.43	7.71	0.030	3588.92	0.0203	3.11
CHT-5R4L505R-TWX	5.4	5.0	-10%~+30%	25	13	22	90	135	1.42	8.21	0.030	3272.73	0.0203	2.55
CHT-5R4L755R-TW	5.4	7.5	-10%~+30%	25	13	27	95	115	1.30	9.00	0.040	3692.70	0.0304	3.68
CHT-5R4L755R-TWX	5.4	7.5	-10%~+30%	25	13	32	60	100	1.97	13.5	0.050	3300.00	0.0304	3.82
5.5V Series-Connected SuperCapacitors Modules														
CHT-5R5L474R-TW	5.5	0.47	-0%~+100%	16	8	14	320	480	0.47	1.05	0.006	3601	0.0020	0.94
CHT-5R5L504R-TW	5.5	0.50	-0%~+100%	16	8	14	320	400	0.50	1.08	0.006	3601	0.0021	1.00
CHT-5R5L105R-TW	5.5	1.0	-0%~+100%	16	8	18	240	360	0.61	2.02	0.010	4001	0.0042	1.67
CHT-5R5L155R-TW	5.5	1.5	-0%~+100%	16	8	22	200	300	0.74	2.84	0.012	3974	0.0063	2.07
CHT-5R5L255R-TWX	5.5	2.5	-0%~+100%	16	8	27	180	270	0.87	4.10	0.015	3283	0.0105	2.56
CHT-5R5L255R-TW	5.5	2.5	-0%~+100%	20	10	22	150	225	0.97	4.40	0.015	3201	0.0105	2.08
CHT-5R5L355R-TWX	5.5	3.5	-0%~+100%	20	10	27	120	180	1.20	5.90	0.020	3492	0.0147	2.55
CHT-5R5L355R-TW	5.5	3.5	-0%~+100%	20	10	22	140	200	1.00	5.55	0.022	3429	0.0147	2.92
CHT-5R5L505R-TW	5.5	5.0	-10%~+30%	20	10	27	120	180	1.20	7.24	0.030	3492	0.0210	3.64
CHT-5R5L505R-TWX	5.5	5.0	-10%~+30%	25	13	22	90	135	1.42	8.21	0.030	3461	0.0210	2.70
CHT-5R5L505R-TWQ	5.5	5.0	-10%~+30%	20	10	32	90	150	1.43	7.71	0.030	3461	0.0210	3.18
CHT-5R5L755R-TW	5.5	7.5	-10%~+30%	25	13	27	95	115	1.30	9.00	0.060	2180	0.0336	3.63
CHT-5R5L805R-TW	5.5	8.0	-10%~+30%	25	13	27	80	120	1.66	10.86	0.040	3741	0.0315	3.90
CHT-5R5L106R-TW	5.5	10	-10%~+30%	25	13	32	70	105	1.93	13.41	0.055	3658	0.0420	4.45
CHT-5R5L126R-TW	5.5	12.5	-10%~+30%	32	16	32	50	75	2.41	17.74	0.068	2955	0.0525	3.21
CHT-5R5L156R-TW	5.5	15	-10%~+30%	32	16	32	40	60	2.92	21.71	0.075	3350	0.0630	3.49
CHT-5R5L256R-TW	5.5	25	-10%~+30%	36	18	42	32	48	3.96	31.25	0.105	2739	0.1050	3.80
CHT-5R5L306R-TW	5.5	30	-10%~+30%	36	18	42	30	42	4.34	33.00	0.120	2503	0.1260	4.30
CHT-5R5L506R-TW	5.5	50	-10%~+30%	36	18	62	26	39	5.30	46.61	0.240	2062	0.2101	4.65

Note: Passive balance is added. Balance options can be provided upon request, and customers can choose according to their application.

: Products with "" only support high temperature 85°C at 5.0V. If you need to use it at a temperature of 85°C and a humidity of 85%, please contact us (85°C & RH 85%).





LIFE TIME AND TEMPERATURE PERFORMANCE

The life of a Super Capacitor is impacted by a combination of operating voltage and the operating temperature according to the following equation :

$$L = L_0 \times 3.25^{\frac{T_0 - T}{10}} \times 1.52^{\frac{V_0 - V}{0.1}}$$

L : is the theoretical lifetime at T temperature;


L₀ : is the working life of the highest rated working temperature;

T : is the actual working temperature;

T₀ : is the highest rated working temperature;

V : is the actual working voltage;

V₀ : is the highest rated working voltage.



*Note : Estimated lifespan: The estimated lifespan under different operating voltages and operating temperatures in a theoretical environment. For the actual service life, please contact us to discuss the working conditions.



SAFETY RECOMMENDATIONS

WARNINGS

- To Avoid Short Circuit, after usage or test, SuperCapacitors voltage needs to discharge to $\leq 0.1V$.
- Do not Apply Over-voltage, Reverse Charge, Burn or Heat Higher than $150^{\circ}C$, explosion-proof valve may break open.
- Do not Press, Damage or disassemble the SuperCapacitor, housing could heat to high temperature causing Burns.
- If you observe Overheating or Burning Smell from the capacitor disconnect Power immediately, and do not touch.

PRECAUTIONS FOR WELDING

When soldering supercapacitors to a PCB, the temperature & time that the body of the supercapacitor sees during soldering can have a negative effect on performance. We advise following these guidelines:

- Do not immerse the supercapacitors in solder. Only the leads should come in contact with the solder.
- Ensure that the body of the supercapacitor is never in contact with the molten solder, the PCB or other components during soldering.
- Excessive temperatures or excessive temperature cycling during soldering may cause the safety vent to burst or the case to shrink or crack, potentially damaging the PCB or other components, and significantly reduce the life of the capacitor.

HAND SOLDERING

Keep distance between the supercapacitor body and the tip of the soldering iron and the tip should never touch the body of the capacitor. Contact between supercapacitor body and soldering iron will cause extensive damage to the supercapacitor, and change its electrical properties. It is recommended that the soldering iron temperature should be less than $350^{\circ}C$, and contact time should be limited to less than 4 seconds. Too much exposure to terminal heat during soldering can cause heat to transfer to the body of the supercapacitor, potentially damaging the electrical properties of the supercapacitor.

REGULATORY

- MSDS
- RoHS Compliant
- Reach Compliant

TRANSPORTATION

Not subjected to US DOT or IATA regulations
 UN3499, <10Wh, Non-Hazardous Goods
 International shipping description –
 "Electronic Products – Capacitor"

WAVE SOLDERING

Only use wave soldering on Radial type supercapacitors. The PCB should be preheated only from the bottom and for less than 60 seconds, with temperature at, or below, $100^{\circ}C$ on the top side of the board for PCBs equal to or greater than 0.8 mm thick.

Solder Temperature ($^{\circ}C$)	Suggested Solder Time (s)	Maximum Solder Time (s)
220	7	9
240	7	9
250	5	7
260	3	5

REFLOW SOLDERING

Infrared or conveyor over reflow techniques can be used on these supercapacitors. Do not use a traditional reflow oven without clear rated reflow temperature for supercapacitors.