



## N-Channel Enhancement Mode Power MOSFET

<p><b>Description</b></p> <p>The GT035N10T uses advanced trench technology to provide excellent <math>R_{DS(ON)}</math>, low gate charge. It can be used in a wide variety of applications.</p> <p><b>General Features</b></p> <ul style="list-style-type: none"> <li>● <math>V_{DS}</math> 100V</li> <li>● <math>I_D</math> (at <math>V_{GS} = 10V</math>) 190A</li> <li>● <math>R_{DS(ON)}</math> (at <math>V_{GS} = 10V</math>) &lt; 3.5mΩ</li> <li>● 100% Avalanche Tested</li> <li>● RoHS Compliant</li> </ul> <p><b>Application</b></p> <ul style="list-style-type: none"> <li>● Power switch</li> <li>● DC/DC converters</li> </ul>	 <p>Schematic diagram</p>  <p>TO-220</p>
--	--

### Ordering Information

Device	Package	Marking	Packaging
GT035N10T	TO-220	GT035N10	50pcs/Tube

### Absolute Maximum Ratings $T_C = 25^\circ\text{C}$ , unless otherwise noted

Parameter	Symbol	Value	Unit
Drain-Source Voltage	$V_{DS}$	100	V
Continuous Drain Current	$I_D$	190	A
Pulsed Drain Current (note1)	$I_{DM}$	760	A
Gate-Source Voltage	$V_{GS}$	$\pm 20$	V
Power Dissipation	$P_D$	250	W
Single pulse avalanche energy (note2)	$E_{AS}$	441	mJ
Operating Junction and Storage Temperature Range	$T_J, T_{stg}$	-55 To 150	°C

### Thermal Resistance

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-Ambient	$R_{thJA}$	55	°C/W
Maximum Junction-to-Case	$R_{thJC}$	0.5	°C/W


**Specifications**  $T_J = 25^\circ\text{C}$ , unless otherwise noted

Parameter	Symbol	Test Conditions	Value			Unit
			Min.	Typ.	Max.	
<b>Static Parameters</b>						
Drain-Source Breakdown Voltage	$V_{(\text{BR})\text{DSS}}$	$V_{\text{GS}} = 0\text{V}, I_D = 250\mu\text{A}$	100	--	--	V
Zero Gate Voltage Drain Current	$I_{\text{DSS}}$	$V_{\text{DS}} = 100\text{V}, V_{\text{GS}} = 0\text{V}$	--	--	1	$\mu\text{A}$
Gate-Source Leakage	$I_{\text{GSS}}$	$V_{\text{GS}} = \pm 20\text{V}$	--	--	$\pm 100$	nA
Gate-Source Threshold Voltage	$V_{\text{GS}(\text{th})}$	$V_{\text{DS}} = V_{\text{GS}}, I_D = 250\mu\text{A}$	2.0	3.0	4.0	V
Drain-Source On-Resistance	$R_{\text{DS}(\text{on})}$	$V_{\text{GS}} = 10\text{V}, I_D = 30\text{A}$	--	2.85	3.5	$\text{m}\Omega$
Forward Transconductance	$g_{\text{FS}}$	$V_{\text{GS}} = 5\text{V}, I_D = 30\text{A}$	--	65	--	S
<b>Dynamic Parameters</b>						
Input Capacitance	$C_{\text{iss}}$	$V_{\text{GS}} = 0\text{V}, V_{\text{DS}} = 50\text{V}, f = 1.0\text{MHz}$	--	6478	--	pF
Output Capacitance	$C_{\text{oss}}$		--	2015	--	
Reverse Transfer Capacitance	$C_{\text{rss}}$		--	166	--	
Total Gate Charge	$Q_g$	$V_{\text{DD}} = 50\text{V}, I_D = 30\text{A}, V_{\text{GS}} = 10\text{V}$	--	68	--	nC
Gate-Source Charge	$Q_{\text{gs}}$		--	26	--	
Gate-Drain Charge	$Q_{\text{gd}}$		--	31	--	
Turn-on Delay Time	$t_{\text{d}(\text{on})}$	$V_{\text{DD}} = 50\text{V}, I_D = 30\text{A}, R_G = 3\Omega$	--	27	--	ns
Turn-on Rise Time	$t_r$		--	21	--	
Turn-off Delay Time	$t_{\text{d}(\text{off})}$		--	78	--	
Turn-off Fall Time	$t_f$		--	30	--	
<b>Drain-Source Body Diode Characteristics</b>						
Continuous Body Diode Current	$I_S$	$T_C = 25^\circ\text{C}$	--	--	190	A
Body Diode Voltage	$V_{\text{SD}}$	$T_J = 25^\circ\text{C}, I_{\text{SD}} = 30\text{A}, V_{\text{GS}} = 0\text{V}$	--	--	1.2	V
Reverse Recovery Charge	$Q_{\text{rr}}$	$I_F = 30\text{A}, V_{\text{GS}} = 0\text{V}$ $di/dt = 100\text{A}/\mu\text{s}$	--	680	--	nC
Reverse Recovery Time	$T_{\text{rr}}$		--	132	--	ns



**Notes**

1. Repetitive Rating: Pulse width limited by maximum junction temperature
2. EAS condition :  $T_J=25^\circ\text{C}$ ,  $V_{\text{DD}}=50\text{V}$ ,  $V_{\text{GS}}=10\text{V}$ ,  $L=0.5\text{mH}$ ,  $R_G=25\Omega$
3. Identical low side and high side switch with identical  $R_G$



### Gate Charge Test Circuit



### Switch Time Test Circuit




### EAS Test Circuit




**Typical Characteristics**  $T_J = 25^\circ\text{C}$ , unless otherwise noted


**Figure 1. Output Characteristics**




**Figure 2. Transfer Characteristics**




**Figure 3. Drain Source On Resistance**




**Figure 4. Gate Charge**



**Figure 5. Capacitance**




**Figure 6. Source-Drain Diode Forward**




**Typical Characteristics**  $T_J = 25^\circ\text{C}$ , unless otherwise noted


**Figure 7. Drain-Source On-Resistance**




**Figure 8. Safe Operation Area**



**Figure 9. Normalized Maximum Transient Thermal Impedance**



## TO-220 Package Information



### COMMON DIMENSIONS

SYMBOL	mm		
	MIN	NOM	MAX
A	4.37	4.57	4.77
A <sub>1</sub>	1.22	1.27	1.42
A <sub>2</sub>	2.49	2.69	2.89
b	0.75	0.81	0.96
b <sub>2</sub>	1.22	1.27	1.47
c	0.30	0.38	0.48
D <sub>1</sub>	8.50	8.70	8.90
D <sub>2</sub>	5.20	—	—
E	9.86	10.16	10.36
E <sub>5</sub>	7.06	—	—
e	2.54BSC		
e <sub>1</sub>	5.08BSC		
H <sub>1</sub>	6.10	6.30	6.50
L	13.10	13.40	13.70
L <sub>1</sub>	—	3.75	4.10
$\Phi P$	3.70	3.84	3.99
Q	2.54	2.74	2.94