

# Precision Operational Amplifier, 10 $\mu$ V, Zero-Drift, 1.6 V to 5.5 V Supply, 1.5 MHz

## NCS21801, NCS21802, NCS21803, NCS21804

The NCS21801, NCS21802, NCS21803, and NCS21804 are precision op amps featuring low input offset voltage and low offset drift over time and temperature. The common mode voltage range extends 100 mV beyond the supply rails, which makes it suitable for both high-side and low-side current sensing applications.




The NCS2180x is available in single, dual, and quad channel configurations. All versions are specified for operation from  $-40^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$ . NCV prefix parts are automotive grade 1 qualified and offer performance over the extended temperature range from  $-40^{\circ}\text{C}$  to  $+150^{\circ}\text{C}$ .

### Features

- Input Offset Voltage:  $\pm 10 \mu\text{V}$  max
- Offset Voltage Drift Over Temperature:  $\pm 5 \text{ nV}/^{\circ}\text{C}$  Typical
- Common Mode Input Voltage Range:  $V_{\text{SS}} - 0.1 \text{ V}$  to  $V_{\text{DD}} + 0.1 \text{ V}$
- Supply Voltage Range: 1.8 V to 5.5 V
- Extended Supply Voltage Range: 1.6 V to 5.5 V for  $T_{\text{A}} = 0^{\circ}\text{C}$  to  $85^{\circ}\text{C}$
- Unity Gain Bandwidth: 1.5 MHz
- Quiescent Consumption: 100  $\mu\text{A}$  Max per Channel
- Enable Function Available on NCS21803
- NCV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q100 Qualified and PPAP Capable
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant

### Applications

- High-Side Current Sensing
- Low-Side Current Sensing
- Difference Amplifier
- Instrumentation Amplifier
- Power Management
- Automotive



### DEVICE MARKING INFORMATION

See general marking information in the device marking section on page 2 of this data sheet.

### PIN CONNECTIONS


See pin connections on page 3 of this data sheet.

### ORDERING INFORMATION

See detailed ordering and shipping information on page 2 of this data sheet.

# NCS21801, NCS21802, NCS21803, NCS21804

## DEVICE MARKING INFORMATION



XX = Specific Device Code  
A = Assembly Location  
Y = Year  
W = Work Week  
M = Date Code  
G or ■ = Pb-Free Package

(Note: Microdot may be in either location)

## ORDERING INFORMATION


| Channels                       | Enable | Package                      | Part Number    | Marking | Shipping           |
|--------------------------------|--------|------------------------------|----------------|---------|--------------------|
| <b>INDUSTRIAL AND CONSUMER</b> |        |                              |                |         |                    |
| Single                         | No     | SOT23-5 / TSOP-5             | NCS21801SN2T1G | ACC     | 3000 / Tape & Reel |
|                                |        | SC70-5 / SC-88-5 / SOT-353-5 | NCS21801SQ3T2G | AAU     |                    |
|                                | Yes    | SC-88 / SC70-6 / SOT-363     | NCS21803SQT2G  | AAE     |                    |
| Dual                           | No     | UDFN-8                       | NCS21802MUTBG  | AAJ     | 3000 / Tape & Reel |
|                                |        | Micro8                       | NCS21802DMR2G  | 802     | 4000 / Tape & Reel |
| Quad                           | No     | TSSOP-14                     | NCS21804DTBR2G | 804     | 2500 / Tape & Reel |
| <b>AUTOMOTIVE QUALIFIED</b>    |        |                              |                |         |                    |
| Single                         | No     | SOT23-5 / TSOP-5             | NCV21801SN2T1G | ACC     | 3000 / Tape & Reel |
|                                |        | SC70-5 / SC-88-5 / SOT-353-5 | NCV21801SQ3T2G | AAU     |                    |
| Dual                           | No     | Micro8                       | NCV21802DMR2G  | 802     | 4000 / Tape & Reel |
| Quad                           | No     | TSSOP-14                     | NCV21804DTBR2G | 804     | 2500 / Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.


# NCS21801, NCS21802, NCS21803, NCS21804

## PIN CONNECTIONS


**Single Channel Configuration  
NCS21801**




**Single Channel with Enable Configuration  
NCS21803**



**Dual Channel Configuration  
NCS21802**



**Quad Channel Configuration  
NCS21804**



# NCS21801, NCS21802, NCS21803, NCS21804

## MAXIMUM RATINGS (Note 1)

| Parameter                                     | Symbol                     | Rating                               | Unit |
|-----------------------------------------------|----------------------------|--------------------------------------|------|
| Supply Voltage ( $V_{DD} - V_{SS}$ ) (Note 1) | $V_S$                      | -0.3 to 6                            | V    |
| Input Voltage (Note 2)                        | $V_{IN+}, V_{IN-}, V_{EN}$ | $(V_{SS} - 0.3)$ to $(V_{DD} + 0.3)$ | V    |
| Differential Input Voltage                    | $V_{IN+}, V_{IN-}$         | $\pm (V_{DD} - V_{SS} + 0.3)$        | V    |
| Output Voltage (Note 2)                       | $V_{OUT}$                  | $(V_{SS} - 0.3)$ to $(V_{DD} + 0.3)$ | V    |
| Output Short Circuit Current (Note 3)         | $I_{OUT}$                  | Continuous                           |      |
| Input Current into Any Pin (Note 2)           | $I_{IN}$                   | $\pm 10$                             | mA   |
| Maximum Junction Temperature                  | $T_{J(max)}$               | +150                                 | °C   |
| Storage Temperature Range                     | $T_{STG}$                  | -65 to +150                          | °C   |
| ESD Human Body Model (Note 4)                 | HBM                        | $\pm 2000$                           | V    |
| Charged Device Model (Note 4)                 | CDM                        | $\pm 1000$                           | V    |
| Latch-up Current (Note 5)                     |                            | 100                                  | mA   |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Refer to ELECTRICAL CHARACTERISTICS, RECOMMENDED OPERATING RANGES and/or APPLICATION INFORMATION for safe operating parameters
2. Terminals are diode-clamped to the power-supply rails. Input signals that can swing more than 0.3 V beyond the supply rails should be current limited to  $\pm 10$  mA or less. Output terminals should not be driven by external sources.
3. Short circuits to either rail can cause an increase in the junction temperature. The total power dissipation must be limited to prevent the junction temperature from exceeding the 150°C limit.
4. This device series incorporates ESD protection and is tested by the following methods:  
ESD Human Body Model tested per JEDEC standard JS-001-2017 (AEC-Q100-002)  
ESD Charged Device Model tested per JEDEC standard JS-002-2014 (AEC-Q100-011)
5. Latch-up Current tested per JEDEC standard: JESD78E.

## THERMAL CHARACTERISTICS (Notes 6, 7)

| Package                      | $\theta_{JA}$<br>Junction-to-Ambient<br>Thermal Resistance | $\Psi_{JT}$<br>Junction-to-Case Top<br>Thermal Characteristic | $\Psi_{JB}$<br>Junction-to-Board<br>Thermal Characteristic | Unit |
|------------------------------|------------------------------------------------------------|---------------------------------------------------------------|------------------------------------------------------------|------|
| TSOP-5 / SOT23-5             | 188                                                        | 26                                                            | 38                                                         | °C/W |
| SC70-5 / SC-88-5 / SOT-353-5 | 241                                                        | 46                                                            | 64                                                         |      |
| SC-88 / SC70-6 / SOT-363     | 230                                                        | 45                                                            | 60                                                         |      |
| UDFN8                        | 105                                                        | 10                                                            | 51                                                         |      |
| Micro8 / MSOP-8              | 105                                                        | 24                                                            | 96                                                         |      |
| TSSOP-14                     | 86                                                         | 9                                                             | 53                                                         |      |

6. Refer to ELECTRICAL CHARACTERISTICS, RECOMMENDED OPERATING RANGES and/or APPLICATION INFORMATION for safe operating parameters
7. Mounted on a JESD51-7 thermal board, 2S2P, 1 in<sup>2</sup> copper spreader area, 1 oz signal plane thickness

## RECOMMENDED OPERATING RANGES

| Parameter                            | Symbol   | Conditions             | Min            | Max            | Unit |
|--------------------------------------|----------|------------------------|----------------|----------------|------|
| Ambient Temperature                  | $T_A$    | NCS prefix             | -40            | 125            | °C   |
|                                      |          | NCV prefix             | -40            | 150 (Note 8)   |      |
| Common Mode Input Voltage            | $V_{CM}$ | Full temperature range | $V_{SS} - 0.1$ | $V_{DD} + 0.1$ | V    |
| Supply Voltage ( $V_{DD} - V_{SS}$ ) | $V_S$    | $T_A = 0$ to 85°C      | 1.6            | 5.5            | V    |
|                                      |          | Full temperature range | 1.8            | 5.5            |      |

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

8. Operation up to  $T_A = 150^\circ\text{C}$  is permitted, provided the total power dissipation is limited to prevent the junction temperature from exceeding the 150°C absolute maximum limit.

# NCS21801, NCS21802, NCS21803, NCS21804

**ELECTRICAL CHARACTERISTICS** At  $T_A = +25^\circ\text{C}$ ,  $V_S = 1.8\text{ V to }5.5\text{ V}$ , and  $V_{CM} = V_{OUT} = \text{mid-supply}$ , unless otherwise noted.  
**Boldface** limits apply over the specified temperature range, unless otherwise noted, guaranteed by characterization and/or design.

| Parameter                                  | Symbol       | Conditions                                                                         | Temp ( $^\circ\text{C}$ ) | Min        | Typ      | Max        | Unit                       |
|--------------------------------------------|--------------|------------------------------------------------------------------------------------|---------------------------|------------|----------|------------|----------------------------|
| <b>INPUT</b>                               |              |                                                                                    |                           |            |          |            |                            |
| Input Offset Voltage                       | $V_{OS}$     | $V_S = 3.3\text{ V}$                                                               | 25                        |            | $\pm 2$  | $\pm 10$   | $\mu\text{V}$              |
| Input Offset Voltage Drift vs. Temperature | $dV_{OS}/dT$ | $V_S = 1.8\text{ V to }5.5\text{ V}$                                               | -40 to 125                |            | $\pm 5$  | $\pm 75$   | $\text{nV}/^\circ\text{C}$ |
|                                            |              |                                                                                    | -40 to 150                |            | $\pm 5$  | $\pm 75$   |                            |
| Common Mode Rejection Ratio                | CMRR         | $V_S = 1.8\text{ V},$<br>$V_{CM} = V_{SS} - 0.1\text{ V to }V_{DD} + 0.1\text{ V}$ | 25                        | 106        | 131      |            | dB                         |
|                                            |              |                                                                                    | -40 to 125                | <b>100</b> |          |            |                            |
|                                            |              |                                                                                    | -40 to 150                | <b>100</b> |          |            |                            |
|                                            |              | $V_S = 3.3\text{ V},$<br>$V_{CM} = V_{SS} - 0.1\text{ V to }V_{DD} + 0.1\text{ V}$ | 25                        | 113        | 134      |            |                            |
|                                            |              |                                                                                    | -40 to 125                | <b>110</b> |          |            |                            |
|                                            |              |                                                                                    | -40 to 150                | <b>110</b> |          |            |                            |
|                                            |              | $V_S = 5.5\text{ V},$<br>$V_{CM} = V_{SS} - 0.1\text{ V to }V_{DD} + 0.1\text{ V}$ | 25                        | 111        | 137      |            |                            |
|                                            |              |                                                                                    | -40 to 125                | <b>108</b> |          |            |                            |
|                                            |              |                                                                                    | -40 to 150                | <b>108</b> |          |            |                            |
| Input Bias Current (Note 9)                | $I_{IB}$     |                                                                                    | 25                        |            | $\pm 60$ | $\pm 200$  | $\text{pA}$                |
|                                            |              |                                                                                    | -40 to 125                |            |          | $\pm 600$  |                            |
|                                            |              |                                                                                    | -40 to 150                |            |          | $\pm 5000$ |                            |
| Input Offset Current (Note 9)              | $I_{OS}$     |                                                                                    | 25                        |            | $\pm 60$ | $\pm 300$  | $\text{pA}$                |
|                                            |              |                                                                                    | -40 to 125                |            |          | $\pm 400$  |                            |
|                                            |              |                                                                                    | -40 to 150                |            |          | $\pm 2500$ |                            |
| Input Capacitance                          | $C_{IN}$     | Differential                                                                       | 25                        |            | 5        |            | $\text{pF}$                |
|                                            |              | Common mode                                                                        | 25                        |            | 5        |            |                            |

## ENABLE (Note 10)

|                              |            |          |            |                |   |                |    |
|------------------------------|------------|----------|------------|----------------|---|----------------|----|
| Input Voltage Low Threshold  | $V_{EN-L}$ | Shutdown | -40 to 125 |                |   | $V_{SS} + 0.5$ | V  |
| Input Voltage High Threshold | $V_{EN-H}$ | Enabled  | -40 to 125 | $V_{SS} + 1.3$ |   |                | V  |
| Input Leakage Current        | $I_{EN}$   |          | 25         |                | 1 | 100            | nA |

## OUTPUT CHARACTERISTICS

|                        |           |                                    |            |            |     |  |    |
|------------------------|-----------|------------------------------------|------------|------------|-----|--|----|
| Open Loop Voltage Gain | $A_{VOL}$ | $V_S = 1.8\text{ V}$               | 25         | 108        | 133 |  | dB |
|                        |           |                                    | -40 to 125 | <b>106</b> |     |  |    |
|                        |           |                                    | -40 to 150 | <b>106</b> |     |  |    |
|                        |           | $V_S = 3.3\text{ V}, 5.5\text{ V}$ | 25         | 120        | 143 |  |    |
|                        |           |                                    | -40 to 125 | <b>110</b> |     |  |    |
|                        |           |                                    | -40 to 150 | <b>110</b> |     |  |    |

9. Guaranteed by characterization and/or design.

10. The enable function is available on NCS21803 only. The EN pin must be connected to a logic low or logic high voltage.

11. Shutdown Time ( $t_{OFF}$ ) and Enable Time ( $t_{ON}$ ) are defined as the time between the 50% point of the signal applied to the EN pin and the point at which the output voltage reaches within 10% of its final value.

# NCS21801, NCS21802, NCS21803, NCS21804

**ELECTRICAL CHARACTERISTICS** At  $T_A = +25^\circ\text{C}$ ,  $V_S = 1.8\text{ V}$  to  $5.5\text{ V}$ , and  $V_{CM} = V_{OUT} = \text{mid-supply}$ , unless otherwise noted. **Boldface** limits apply over the specified temperature range, unless otherwise noted, guaranteed by characterization and/or design.

| Parameter                                                 | Symbol            | Conditions                                                                                  | Temp ( $^\circ\text{C}$ ) | Min | Typ        | Max        | Unit |
|-----------------------------------------------------------|-------------------|---------------------------------------------------------------------------------------------|---------------------------|-----|------------|------------|------|
| <b>OUTPUT CHARACTERISTICS</b>                             |                   |                                                                                             |                           |     |            |            |      |
| Output Voltage High, Referenced from $V_{DD}$ Supply Rail | $V_{DD} - V_{OH}$ | $I_{OUT} = 30\text{ }\mu\text{A}$                                                           | 25                        |     | 1          | 5          | mV   |
|                                                           |                   |                                                                                             | -40 to 125                |     |            | <b>10</b>  |      |
|                                                           |                   |                                                                                             | -40 to 150                |     |            | <b>10</b>  |      |
|                                                           |                   | $V_S = 3.3\text{ V}$ , $I_{OUT} = 3\text{ mA}$                                              | 25                        |     | 55         | 100        |      |
|                                                           |                   |                                                                                             | -40 to 125                |     |            | <b>125</b> |      |
|                                                           |                   |                                                                                             | -40 to 150                |     |            | <b>125</b> |      |
| Output Voltage Low, Referenced to $V_{SS}$ Supply Rail    | $V_{OL} - V_{SS}$ | $I_{OUT} = 30\text{ }\mu\text{A}$                                                           | 25                        |     | 1          | 5          | mV   |
|                                                           |                   |                                                                                             | -40 to 125                |     |            | <b>10</b>  |      |
|                                                           |                   |                                                                                             | -40 to 150                |     |            | <b>10</b>  |      |
|                                                           |                   | $V_S = 3.3\text{ V}$ , $I_{OUT} = 3\text{ mA}$                                              | 25                        |     | 55         | 100        |      |
|                                                           |                   |                                                                                             | -40 to 125                |     |            | <b>125</b> |      |
|                                                           |                   |                                                                                             | -40 to 150                |     |            | <b>125</b> |      |
| Output Current Sourcing Capability                        | $I_O$             | $V_S = 1.8\text{ V}$                                                                        | 25                        |     | 24         |            | mA   |
|                                                           |                   | $V_S = 3.3\text{ V}$                                                                        | 25                        |     | 29         |            |      |
|                                                           |                   | $V_S = 5.5\text{ V}$                                                                        | 25                        |     | 32         |            |      |
| Output Current Sinking Capability                         | $I_O$             | $V_S = 1.8\text{ V}$                                                                        | 25                        |     | 28         |            |      |
|                                                           |                   | $V_S = 3.3\text{ V}$                                                                        | 25                        |     | 32         |            |      |
|                                                           |                   | $V_S = 5.5\text{ V}$                                                                        | 25                        |     | 38         |            |      |
| Capacitive Load Capability                                | $C_L$             | $A_V = -1$ , $V_{IN} = 100\text{ mVpp}$ step<br>$A_V = 1$ , $V_{IN} = 100\text{ mVpp}$ step | 25                        |     | 400<br>125 |            | pF   |

## DYNAMIC RESPONSE

|                        |          |                                            |    |  |             |  |                  |
|------------------------|----------|--------------------------------------------|----|--|-------------|--|------------------|
| Unity Gain Bandwidth   | BW       | $C_L = 20\text{ pF}$                       | 25 |  | 1.5         |  | MHz              |
| Gain Margin            | $A_M$    | $C_L = 20\text{ pF}$                       | 25 |  | 6           |  | dB               |
| Phase Margin           | $\Phi_M$ | $C_L = 20\text{ pF}$                       | 25 |  | 50          |  | $^\circ$         |
| Slew Rate              | SR       |                                            | 25 |  | 0.7         |  | V/ $\mu\text{s}$ |
| Settling Time          | $t_s$    | 0.1%, $A_V = 1$                            | 25 |  | 20          |  | $\mu\text{s}$    |
| Overload Recovery Time | $t_{OR}$ | $V_{IN} * \text{GAIN} > V_S$               | 25 |  | 200         |  | $\mu\text{s}$    |
| Channel Separation     |          | NCS21802, NCS21804,<br>$f = 10\text{ kHz}$ | 25 |  | 90          |  | dB               |
| EMI Rejection Ratio    | EMIRR    |                                            | 25 |  | See Fig. 26 |  | dB               |

## NOISE

|                             |           |                                            |    |  |     |  |                        |
|-----------------------------|-----------|--------------------------------------------|----|--|-----|--|------------------------|
| Voltage Noise Density       | $e_N$     | $V_S = 3.3$ , $f_{in} = 1\text{ kHz}$      | 25 |  | 42  |  | nV/ $\sqrt{\text{Hz}}$ |
| Voltage Noise, Peak-to-Peak | $e_{P-P}$ | $f_{in} = 0.1\text{ Hz}$ to $10\text{ Hz}$ | 25 |  | 400 |  | nV <sub>PP</sub>       |
| Current Noise Density       | $i_N$     | $f_{in} = 1\text{ kHz}$                    | 25 |  | 445 |  | fA/ $\sqrt{\text{Hz}}$ |

9. Guaranteed by characterization and/or design.

10. The enable function is available on NCS21803 only. The EN pin must be connected to a logic low or logic high voltage.

11. Shutdown Time ( $t_{OFF}$ ) and Enable Time ( $t_{ON}$ ) are defined as the time between the 50% point of the signal applied to the EN pin and the point at which the output voltage reaches within 10% of its final value.

## NCS21801, NCS21802, NCS21803, NCS21804

**ELECTRICAL CHARACTERISTICS** At  $T_A = +25^\circ\text{C}$ ,  $V_S = 1.8\text{ V to }5.5\text{ V}$ , and  $V_{CM} = V_{OUT} = \text{mid-supply}$ , unless otherwise noted. **Boldface** limits apply over the specified temperature range, unless otherwise noted, guaranteed by characterization and/or design.

| Parameter                                      | Symbol    | Conditions                                  | Temp ( $^\circ\text{C}$ ) | Min        | Typ | Max        | Unit          |
|------------------------------------------------|-----------|---------------------------------------------|---------------------------|------------|-----|------------|---------------|
| <b>POWER SUPPLY</b>                            |           |                                             |                           |            |     |            |               |
| Quiescent Current                              | $I_Q$     | NCS21801, NCS2803,<br>no load               | 25                        |            | 75  | 105        | $\mu\text{A}$ |
|                                                |           |                                             | -40 to 125                |            |     | <b>130</b> |               |
|                                                |           |                                             | -40 to 150                |            |     | <b>200</b> |               |
|                                                |           | NCS21802, NCS21804,<br>per channel, no load | 25                        |            | 75  | 100        | $\mu\text{A}$ |
|                                                |           |                                             | -40 to 125                |            |     | <b>125</b> |               |
|                                                |           |                                             | -40 to 150                |            |     | <b>150</b> |               |
| Quiescent Current in Shutdown<br>(Notes 9, 10) | $I_{QSD}$ | Per channel                                 | 25                        |            | 5   | 50         | $\text{nA}$   |
|                                                |           |                                             | -40 to 85                 |            |     | <b>75</b>  |               |
|                                                |           |                                             | -40 to 125                |            |     | <b>200</b> |               |
| Power Supply Rejection Ratio                   | PSRR      | $V_S = 1.8\text{ V to }5.5\text{ V}$        | 25                        | 115        | 140 |            | $\text{dB}$   |
|                                                |           |                                             | -40 to 125                | <b>110</b> |     |            |               |
|                                                |           |                                             | -40 to 150                | <b>110</b> |     |            |               |
| Power Up Time                                  |           | NCS21801, NCS21803                          | 25                        |            | 50  |            | $\mu\text{s}$ |
|                                                |           | NCS21802, NCS21804                          | 25                        |            | 40  |            |               |
| Enable Time (Note 10, 11)                      | $t_{ON}$  |                                             | 25                        |            | 50  |            | $\mu\text{s}$ |
| Shutdown Time (Note 10, 11)                    | $t_{OFF}$ |                                             | 25                        |            | 3   |            | $\mu\text{s}$ |

9. Guaranteed by characterization and/or design.

10. The enable function is available on NCS21803 only. The EN pin must be connected to a logic low or logic high voltage.

11. Shutdown Time ( $t_{OFF}$ ) and Enable Time ( $t_{ON}$ ) are defined as the time between the 50% point of the signal applied to the EN pin and the point at which the output voltage reaches within 10% of its final value.

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

# NCS21801, NCS21802, NCS21803, NCS21804

**ELECTRICAL CHARACTERISTICS** At  $T_A = +25^\circ\text{C}$ ,  $V_S = 1.6\text{ V}$ , and  $V_{CM} = V_{OUT} = \text{mid-supply}$ , unless otherwise noted. **Boldface** limits apply over the specified temperature range,  $T_A = 0^\circ\text{C}$  to  $85^\circ\text{C}$ , guaranteed by characterization and/or design.

| Parameter                                  | Symbol       | Conditions                                                  | Temp ( $^\circ\text{C}$ ) | Min       | Typ      | Max                         | Unit                       |
|--------------------------------------------|--------------|-------------------------------------------------------------|---------------------------|-----------|----------|-----------------------------|----------------------------|
| <b>INPUT</b>                               |              |                                                             |                           |           |          |                             |                            |
| Input Offset Voltage                       | $V_{OS}$     |                                                             | 25                        |           | $\pm 3$  | $\pm 13$                    | $\mu\text{V}$              |
| Input Offset Voltage Drift vs. Temperature | $dV_{OS}/dT$ |                                                             | 0 to 85                   |           | $\pm 5$  | <b><math>\pm 75</math></b>  | $\text{nV}/^\circ\text{C}$ |
| Common Mode Rejection Ratio                | CMRR         | $V_{CM} = V_{SS} - 0.1\text{ V}$ to $V_{DD} + 0.1\text{ V}$ | 25                        | 96        | 123      |                             | dB                         |
|                                            |              |                                                             | 0 to 85                   | <b>94</b> |          |                             |                            |
| Input Bias Current (Note 12)               | $I_{IB}$     |                                                             | 25                        |           | $\pm 30$ | $\pm 160$                   | $\text{pA}$                |
|                                            |              |                                                             | 0 to 85                   |           |          | <b><math>\pm 250</math></b> |                            |
| Input Offset Current (Note 12)             | $I_{OS}$     |                                                             | 25                        |           | $\pm 36$ | $\pm 200$                   | $\text{pA}$                |
|                                            |              |                                                             | 0 to 85                   |           |          | <b><math>\pm 250</math></b> |                            |
| Input Capacitance                          | $C_{IN}$     | Differential                                                | 25                        |           | 5        |                             | $\text{pF}$                |
|                                            |              | Common mode                                                 | 25                        |           | 5        |                             |                            |

## ENABLE (Note 14)

|                              |            |          |         |                |   |                |    |
|------------------------------|------------|----------|---------|----------------|---|----------------|----|
| Input Voltage Low Threshold  | $V_{EN-L}$ | Shutdown | 0 to 85 |                |   | $V_{SS} + 0.5$ | V  |
| Input Voltage High Threshold | $V_{EN-H}$ | Enabled  | 0 to 85 | $V_{SS} + 1.3$ |   |                | V  |
| Input Leakage Current        | $I_{EN}$   |          | 25      |                | 1 | 100            | nA |

## OUTPUT CHARACTERISTICS

|                                                           |                   |                                                                                             |         |            |            |            |             |
|-----------------------------------------------------------|-------------------|---------------------------------------------------------------------------------------------|---------|------------|------------|------------|-------------|
| Open Loop Voltage Gain                                    | $A_{VOL}$         |                                                                                             | 25      | 106        | 128        |            | dB          |
|                                                           |                   |                                                                                             | 0 to 85 | <b>104</b> |            |            |             |
| Output Voltage High, Referenced from $V_{DD}$ Supply Rail | $V_{DD} - V_{OH}$ | $I_{OUT} = 30\text{ }\mu\text{A}$                                                           | 25      |            | 1          | 5          | mV          |
|                                                           |                   |                                                                                             | 0 to 85 |            |            | <b>10</b>  |             |
|                                                           |                   | $I_{OUT} = 3\text{ mA}$                                                                     | 25      |            | 85         | 130        |             |
|                                                           |                   |                                                                                             | 0 to 85 |            |            | <b>150</b> |             |
| Output Voltage Low, Referenced to $V_{SS}$ Supply Rail    | $V_{OL} - V_{SS}$ | $I_{OUT} = 30\text{ }\mu\text{A}$                                                           | 25      |            | 1          | 5          | mV          |
|                                                           |                   |                                                                                             | 0 to 85 |            |            | <b>10</b>  |             |
|                                                           |                   | $I_{OUT} = 3\text{ mA}$                                                                     | 25      |            | 75         | 130        |             |
|                                                           |                   |                                                                                             | 0 to 85 |            |            | <b>150</b> |             |
| Output Current Sourcing Capability                        | $I_o$             |                                                                                             | 25      |            | 15         |            | mA          |
| Output Current Sinking Capability                         | $I_o$             |                                                                                             | 25      |            | 21         |            |             |
| Capacitive Load Capability                                | $C_L$             | $A_V = -1$ , $V_{IN} = 100\text{ mVpp}$ step<br>$A_V = 1$ , $V_{IN} = 100\text{ mVpp}$ step | 25      |            | 400<br>125 |            | $\text{pF}$ |

## DYNAMIC RESPONSE

|                      |          |                      |    |  |     |  |                        |
|----------------------|----------|----------------------|----|--|-----|--|------------------------|
| Unity Gain Bandwidth | BW       | $C_L = 20\text{ pF}$ | 25 |  | 1.4 |  | MHz                    |
| Gain Margin          | $A_M$    | $C_L = 20\text{ pF}$ | 25 |  | 6   |  | dB                     |
| Phase Margin         | $\Phi_M$ | $C_L = 20\text{ pF}$ | 25 |  | 50  |  | $^\circ$               |
| Slew Rate            | SR       |                      | 25 |  | 0.7 |  | $\text{V}/\mu\text{s}$ |

12. Guaranteed by design and/or characterization.

13. The enable function is available on NCS21803 only. The EN pin must be connected to a logic low or logic high voltage.

14. Shutdown Time ( $t_{OFF}$ ) and Enable Time ( $t_{ON}$ ) are defined as the time between the 50% point of the signal applied to the EN pin and the point at which the output voltage reaches within 10% of its final value.



# NCS21801, NCS21802, NCS21803, NCS21804

**ELECTRICAL CHARACTERISTICS** At  $T_A = +25^\circ\text{C}$ ,  $V_S = 1.6\text{ V}$ , and  $V_{CM} = V_{OUT} = \text{mid-supply}$ , unless otherwise noted. **Boldface** limits apply over the specified temperature range,  $T_A = 0^\circ\text{C}$  to  $85^\circ\text{C}$ , guaranteed by characterization and/or design.

| Parameter | Symbol | Conditions | Temp ( $^\circ\text{C}$ ) | Min | Typ | Max | Unit |
|-----------|--------|------------|---------------------------|-----|-----|-----|------|
|-----------|--------|------------|---------------------------|-----|-----|-----|------|

## DYNAMIC RESPONSE

|                        |          |                                            |    |  |             |  |               |
|------------------------|----------|--------------------------------------------|----|--|-------------|--|---------------|
| Settling Time          | $t_s$    | 0.1%, $A_V = 1$                            | 25 |  | 20          |  | $\mu\text{s}$ |
| Overload Recovery Time | $t_{OR}$ | $V_{IN} * \text{GAIN} > V_S$               | 25 |  | 200         |  | $\mu\text{s}$ |
| Channel Separation     |          | NCS21802, NCS21804,<br>$f = 10\text{ kHz}$ | 25 |  | 90          |  | dB            |
| EMI Rejection Ratio    | EMIRR    |                                            | 25 |  | See Fig. 26 |  | dB            |

## NOISE

|                             |           |                                          |    |  |     |  |                              |
|-----------------------------|-----------|------------------------------------------|----|--|-----|--|------------------------------|
| Voltage Noise Density       | $e_N$     | $f_{in} = 1\text{ kHz}$                  | 25 |  | 53  |  | $\text{nV}/\sqrt{\text{Hz}}$ |
| Voltage Noise, Peak-to-Peak | $e_{P-P}$ | $f_{in} = 0.1\text{ Hz to }10\text{ Hz}$ | 25 |  | 400 |  | $\text{nV}_{PP}$             |
| Current Noise Density       | $i_N$     | $f_{in} = 1\text{ kHz}$                  | 25 |  | 450 |  | $\text{fA}/\sqrt{\text{Hz}}$ |

## POWER SUPPLY

|                                              |           |                                             |         |            |     |            |               |
|----------------------------------------------|-----------|---------------------------------------------|---------|------------|-----|------------|---------------|
| Quiescent Current                            | $I_Q$     | NCS21801, NCS21803,<br>no load              | 25      |            | 70  | 95         | $\mu\text{A}$ |
|                                              |           |                                             | 0 to 85 |            |     | <b>110</b> |               |
|                                              |           | NCS21802, NCS21804,<br>per channel, no load | 25      |            | 65  | 90         |               |
|                                              |           |                                             | 0 to 85 |            |     | <b>105</b> |               |
| Quiescent Current in Shutdown (Notes 12, 13) | $I_{QSD}$ | Per channel                                 | 25      |            | 5   | 50         | $\text{nA}$   |
|                                              |           |                                             | 0 to 85 |            |     | <b>75</b>  |               |
| Power Supply Rejection Ratio                 | PSRR      | $V_S = 1.6\text{ V to }5.5\text{ V}$        | 25      | 115        | 135 |            | dB            |
|                                              |           |                                             | 0 to 85 | <b>110</b> |     |            |               |
| Power Up Time                                |           | NCS21801, NCS21803                          | 25      |            | 75  |            | $\mu\text{s}$ |
|                                              |           | NCS21802, NCS21804                          | 25      |            | 40  |            |               |
| Enable Time (Notes 13, 14)                   | $t_{ON}$  |                                             | 25      |            | 75  |            | $\mu\text{s}$ |
| Shutdown Time (Notes 13, 14)                 | $t_{OFF}$ |                                             | 25      |            | 5   |            | $\mu\text{s}$ |

12. Guaranteed by design and/or characterization.

13. The enable function is available on NCS21803 only. The EN pin must be connected to a logic low or logic high voltage.

14. Shutdown Time ( $t_{OFF}$ ) and Enable Time ( $t_{ON}$ ) are defined as the time between the 50% point of the signal applied to the EN pin and the point at which the output voltage reaches within 10% of its final value.

# TYPICAL CHARACTERISTICS

Typical Performance at  $T_A = 25^\circ\text{C}$ ,  $V_{CM} = \text{mid-supply}$ ,  $C_L = 20 \text{ pF}$ ,  $R_L = 10 \text{ k}\Omega$  to mid-supply, unless otherwise noted




Figure 1. Input Offset Voltage Distribution with 3.3 V Supply




Figure 2. Input Offset Voltage Drift Distribution with 3.3 V Supply




Figure 3. Input Offset Voltage Distribution with 1.6 V Supply





Figure 4. Input Offset Voltage Drift Distribution with 1.6 V Supply


# NCS21801, NCS21802, NCS21803, NCS21804

## TYPICAL CHARACTERISTICS


Typical Performance at  $T_A = 25^\circ\text{C}$ ,  $V_{CM} = \text{mid-supply}$ ,  $C_L = 20 \text{ pF}$ ,  $R_L = 10 \text{ k}\Omega$  to mid-supply, unless otherwise noted




**Figure 5. Input Offset Voltage vs. Temperature at 5.5 V Supply**



**Figure 6. Input Offset Voltage vs. Temperature at 1.8 V Supply**



**Figure 7. Input Offset Voltage vs. Common Mode Voltage at 5.5 V Supply**



**Figure 8. Input Offset Voltage vs. Common Mode Voltage at 1.6 V Supply**

# TYPICAL CHARACTERISTICS

Typical Performance at  $T_A = 25^\circ\text{C}$ ,  $V_{CM} = \text{mid-supply}$ ,  $C_L = 20 \text{ pF}$ ,  $R_L = 10 \text{ k}\Omega$  to mid-supply, unless otherwise noted




Figure 9. Open Loop Gain and Phase vs. Frequency




Figure 10. Closed Loop Gain vs. Frequency




Figure 11. Input Bias Current and Input Offset Current vs. Common Mode Input Voltage




Figure 12. Input Bias Current and Input Offset Current vs. Temperature




Figure 13. Output Voltage Low vs. Output Current at 5.5 V Supply






Figure 14. Output Voltage Low vs. Output Current at 1.6 V Supply

# TYPICAL CHARACTERISTICS


Typical Performance at  $T_A = 25^\circ\text{C}$ ,  $V_{CM} = \text{mid-supply}$ ,  $C_L = 20 \text{ pF}$ ,  $R_L = 10 \text{ k}\Omega$  to mid-supply, unless otherwise noted




**Figure 15. Output Voltage High vs. Output Current at 5.5 V Supply**




**Figure 16. Output Voltage High vs. Output Current at 1.6 V Supply**




**Figure 17. CMRR vs. Frequency**



**Figure 18. PSRR vs. Frequency**



**Figure 19. 0.1 Hz to 10 Hz Noise**



**Figure 20. Voltage Noise Density vs. Frequency**

## TYPICAL CHARACTERISTICS

Typical Performance at  $T_A = 25^\circ\text{C}$ ,  $V_{CM} = \text{mid-supply}$ ,  $C_L = 20 \text{ pF}$ ,  $R_L = 10 \text{ k}\Omega$  to mid-supply, unless otherwise noted




Figure 21. Current Noise Density vs. Frequency




Figure 22. THD+n vs. Frequency




Figure 23. Open Loop Output Impedance vs. Frequency




Figure 24. Small Signal Overshoot vs. Load Capacitance




Figure 25. Channel Separation vs. Frequency






Figure 26. EMIRR vs. Frequency

# TYPICAL CHARACTERISTICS


Typical Performance at  $T_A = 25^\circ\text{C}$ ,  $V_{CM} = \text{mid-supply}$ ,  $C_L = 20 \text{ pF}$ ,  $R_L = 10 \text{ k}\Omega$  to mid-supply, unless otherwise noted




**Figure 27. Quiescent Current Per Channel vs. Temperature**




**Figure 28. Quiescent Current Per Channel vs. Supply Voltage**




**Figure 29. Inverting Small Signal Step Response with  $V_S = 3.3 \text{ V}$  (Split Supplies)**



**Figure 30. Non-Inverting Small Signal Step Response with  $V_S = 3.3 \text{ V}$  (Split Supplies)**



**Figure 31. Inverting Large Signal Step Response with  $V_S = 3.3 \text{ V}$  (Split Supply)**



**Figure 32. Non-Inverting Large Signal Step Response with  $V_S = 3.3 \text{ V}$  (Split Supply)**

# TYPICAL CHARACTERISTICS

Typical Performance at  $T_A = 25^\circ\text{C}$ ,  $V_{CM} = \text{mid-supply}$ ,  $C_L = 20\text{ pF}$ ,  $R_L = 10\text{ k}\Omega$  to mid-supply, unless otherwise noted




Figure 33. Power Up Time with 5.5 V Supply




Figure 34. Power Up Time with 1.6 V Supply




Figure 35. Output Overload Recovery with  $V_S = 3.3\text{ V}$  (Split Supply)




Figure 36. Settling Time with  $V_S = 3.3\text{ V}$  (Split Supply)




Figure 37. Large Signal Gain vs. Frequency





Figure 38. Unity Gain Bandwidth vs. Input Common Mode Voltage



**TYPICAL CHARACTERISTICS**

Typical Performance at  $T_A = 25^\circ\text{C}$ ,  $V_{CM} = \text{mid-supply}$ ,  $C_L = 20\text{ pF}$ ,  $R_L = 10\text{ k}\Omega$  to mid-supply, unless otherwise noted



**Figure 39. Shutdown Current vs. Temperature**

# TYPICAL CHARACTERISTICS

Typical Performance at  $T_A = 25^\circ\text{C}$ ,  $V_{CM} = \text{mid-supply}$ ,  $C_L = 20 \text{ pF}$ ,  $R_L = 10 \text{ k}\Omega$  to mid-supply, unless otherwise noted




Figure 40. Shutdown Time with  $V_S = 5.5 \text{ V}$  (Split Supply)




Figure 41. Shutdown Time with  $V_S = 1.6 \text{ V}$  (Split Supply)




Figure 42. Enable Time with  $V_S = 5.5 \text{ V}$  (Split Supply)





Figure 43. Enable Time with  $V_S = 1.6 \text{ V}$  (Split Supply)

## APPLICATIONS INFORMATION

The NCS21801, NCS21802, NCS21803, and NCS21804 precision amplifiers feature low input offset voltage and zero-drift over temperature. The input common mode voltage range extends 100 mV beyond the rails, allowing for measurements at ground or the supply voltage. These characteristics make the NCS21801 series well-suited for applications such as current sensing and sensor interface. The NCS21803 additionally features an enable pin that allows the amplifier to enter shutdown mode to reduce current consumption in low power applications.

**Architecture**

The low input offset voltage and zero-drift characteristics of amplifiers in the NCS21801 series is achieved through the chopper-stabilized architecture. Unlike the classical chopper architecture, the chopper-stabilized architecture has two signal paths to take advantage of both precision and speed.



**Figure 44. Simplified Schematic of the Chopper-stabilized Amplifier Architecture**

In Figure 44, the lower signal path is where the chopper samples the input offset voltage, which is then used to correct the offset at the output. The offset correction occurs at a frequency of 100 kHz. Due to this periodic sampling, the chopper-stabilized architecture is optimized for best performance at frequencies up to the related Nyquist frequency (1/2 of the offset correction frequency). As the signal frequency exceeds the Nyquist frequency, 50 kHz, aliasing may occur at the output. This is an inherent limitation of all chopper and chopper-stabilized architectures. Nevertheless, the NCS2180x is designed to minimize aliasing beyond the Nyquist frequency. ON Semiconductor's patented approach utilizes two cascaded, symmetrical, RC notch filters tuned to the chopper frequency and its fifth harmonic to reduce aliasing effects.

The feed-forward path, which is shown as the upper signal path of the block diagram in Figure 44, is the high speed signal path that extends the gain bandwidth to 1.5 MHz. Not only does this help retain high frequency components of the input signal, but it also improves the loop gain at low frequencies. This is especially useful for low-side current sensing and sensor interface applications

where the signal is low frequency and the differential voltage is relatively small.

Both internal amplifiers have specialized circuitry to maintain nearly constant bandwidth, noise, and slew rate over the entire common mode voltage range. This also improves the overall input offset voltage, PSRR, and CMRR performance, while significantly reducing the THD+noise level. These characteristics are very useful in signal processing.

**Input Offset Voltage**

Input offset voltage is an intrinsic op amp characteristic that arises from mismatches in the IN+ and IN- paths. Since the NCS2180x series amplifiers have such low input offset voltage to begin with, external factors can have a non-trivial contribution to the effective input offset voltage. Conditions created by the physical environment can create package stress, thereby influencing the input offset voltage. These factors include air flow and PCB construction. Taking these factors into consideration, the input offset voltage performance should be validated in the application environment.

### EMIRR

The NCS21801 series has built-in input filters to reduce high frequency EMI frequency signals before they enter the amplifier. Under normal circumstances, P-N junctions within the silicon can rectify these high frequency signals, and the effect can be seen as a DC offset at the output. Since this added offset can have a noticeable effect on high precision measurements, EMI rejection ratio (EMIRR) can be used to quantify the robustness of an amplifier to these signals.

### Enable Function

The enable pin on NCS21803 allows the user to put the amplifier into shutdown mode when it is not in use. Setting EN to the logic low level reduces the current consumption down to less than 300 nA, which is useful for portable and

battery-powered applications. The output becomes high impedance. Setting the EN pin to logic high enables the output again, with the output reaching the final value ( $\pm 1\%$ ) according to the specified enable time. A floating EN pin results in an indeterminate output state.

### Layout Recommendations

Bypass capacitors of 0.1  $\mu\text{F}$  to ground should be placed as close as possible to the supply pins.




The UDFN8 package has an exposed leadframe die pad on the underside of the package. This pad should be soldered to the PCB, as shown in the recommended soldering footprint in the Package Dimensions section of this datasheet. The center pad can be electrically connected to VSS or it may be left floating. When connected to VSS, the center pad acts as a heat sink, improving the thermal resistance of the part.



SCALE 2:1

SC-88A (SC-70-5/SOT-353)  
CASE 419A-02  
ISSUE M

DATE 11 APR 2023



RECOMMENDED  
MOUNTING FOOTPRINT


\* For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETERS
3. 419A-01 OBSOLETE. NEW STANDARD 419A-02
4. DIMENSIONS D AND E1 DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.1016MM PER SIDE.

| DIM | MILLIMETERS |      |      |
|-----|-------------|------|------|
|     | MIN.        | NOM. | MAX. |
| A   | 0.80        | 0.95 | 1.10 |
| A1  | ---         | ---  | 0.10 |
| A3  | 0.20 REF    |      |      |
| b   | 0.10        | 0.20 | 0.30 |
| c   | 0.10        | ---  | 0.25 |
| D   | 1.80        | 2.00 | 2.20 |
| E   | 2.00        | 2.10 | 2.20 |
| E1  | 1.15        | 1.25 | 1.35 |
| e   | 0.65 BSC    |      |      |
| L   | 0.10        | 0.15 | 0.30 |

GENERIC MARKING  
DIAGRAM\*



\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

XXX = Specific Device Code

M = Date Code

▪ = Pb-Free Package

(Note: Microdot may be in either location)

STYLE 1:

- PIN 1. BASE
2. EMITTER
3. BASE
4. COLLECTOR
5. COLLECTOR

STYLE 2:

- PIN 1. ANODE
2. EMITTER
3. BASE
4. COLLECTOR
5. CATHODE

STYLE 3:

- PIN 1. ANODE 1
2. N/C
3. ANODE 2
4. CATHODE 2
5. CATHODE 1

STYLE 4:

- PIN 1. SOURCE 1
2. DRAIN 1/2
3. SOURCE 1
4. GATE 1
5. GATE 2

STYLE 5:

- PIN 1. CATHODE
2. COMMON ANODE
3. CATHODE 2
4. CATHODE 3
5. CATHODE 4

STYLE 6:

- PIN 1. EMITTER 2
2. BASE 2
3. EMITTER 1
4. COLLECTOR
5. COLLECTOR 2/BASE 1

STYLE 7:

- PIN 1. BASE
2. EMITTER
3. BASE
4. COLLECTOR
5. COLLECTOR

STYLE 8:

- PIN 1. CATHODE
2. COLLECTOR
3. N/C
4. BASE
5. EMITTER

STYLE 9:

- PIN 1. ANODE
2. CATHODE
3. ANODE
4. ANODE
5. ANODE

Note: Please refer to datasheet for style callout. If style type is not called out in the datasheet refer to the device datasheet pinout or pin assignment.

|                  |                          |                                                                                                                                                                                  |
|------------------|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DOCUMENT NUMBER: | 98ASB42984B              | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION:     | SC-88A (SC-70-5/SOT-353) | PAGE 1 OF 1                                                                                                                                                                      |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.








SC-88 2.00x1.25x0.90, 0.65P  
CASE 419B-02  
ISSUE Z

DATE 18 APR 2024

NOTES:


1. DIMENSIONING AND TOLERANCING CONFORM TO ASME Y14.5-2018.
2. ALL DIMENSION ARE IN MILLIMETERS.
3. DIMENSIONS D AND E1 DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.20 PER END.
4. DIMENSIONS D AND E1 AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY AND DATUM H.
5. DATUMS A AND B ARE DETERMINED AT DATUM H.
6. DIMENSIONS b AND c APPLY TO THE FLAT SECTION OF THE LEAD BETWEEN 0.08 AND 0.15 FROM THE TIP.
7. DIMENSION b DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 TOTAL IN EXCESS OF DIMENSION b AT MAXIMUM MATERIAL CONDITION. THE DAMBAR CANNOT BE LOCATED ON THE LOWER RADIUS OF THE FOOT.



RECOMMENDED MOUNTING FOOTPRINT\*

\* FOR ADDITIONAL INFORMATION ON OUR Pb-FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ONSEMI SOLDERING AND MOUNTING TECHNIQUES REFERENCE MANUAL, SOLDERRM/D.

GENERIC  
MARKING DIAGRAM\*



XXX = Specific Device Code  
M = Date Code\*  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

\*Date Code orientation and/or position may vary depending upon manufacturing location.

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

| DIM | MILLIMETERS |      |      |
|-----|-------------|------|------|
|     | MIN.        | NOM. | MAX. |
| A   | ---         | ---  | 1.10 |
| A1  | 0.00        | ---  | 0.10 |
| A2  | 0.70        | 0.90 | 1.00 |
| b   | 0.15        | 0.20 | 0.25 |
| c   | 0.08        | 0.15 | 0.22 |
| D   | 2.00 BSC    |      |      |
| E   | 2.10 BSC    |      |      |
| E1  | 1.25 BSC    |      |      |
| e   | 0.65 BSC    |      |      |
| L   | 0.26        | 0.36 | 0.46 |
| L2  | 0.15 BSC    |      |      |
| aaa | 0.15        |      |      |
| bbb | 0.30        |      |      |
| ccc | 0.10        |      |      |
| ddd | 0.10        |      |      |

STYLES ON PAGE 2

|                  |                             |                                                                                                                                                                                  |
|------------------|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DOCUMENT NUMBER: | 98ASB42985B                 | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION:     | SC-88 2.00x1.25x0.90, 0.65P | PAGE 1 OF 2                                                                                                                                                                      |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

SC-88 2.00x1.25x0.90, 0.65P  
CASE 419B-02  
ISSUE Z


DATE 18 APR 2024

|                                                                                                            |                                                                                                        |                                                                                                             |                                                                                                             |                                                                                                             |                                                                                                       |
|------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|
| STYLE 1:<br>PIN 1. EMITTER 2<br>2. BASE 2<br>3. COLLECTOR 1<br>4. EMITTER 1<br>5. BASE 1<br>6. COLLECTOR 2 | STYLE 2:<br>CANCELLED                                                                                  | STYLE 3:<br>CANCELLED                                                                                       | STYLE 4:<br>PIN 1. CATHODE<br>2. CATHODE<br>3. COLLECTOR<br>4. EMITTER<br>5. BASE<br>6. ANODE               | STYLE 5:<br>PIN 1. ANODE<br>2. ANODE<br>3. COLLECTOR<br>4. EMITTER<br>5. BASE<br>6. CATHODE                 | STYLE 6:<br>PIN 1. ANODE 2<br>2. N/C<br>3. CATHODE 1<br>4. ANODE 1<br>5. N/C<br>6. CATHODE 2          |
| STYLE 7:<br>PIN 1. SOURCE 2<br>2. DRAIN 2<br>3. GATE 1<br>4. SOURCE 1<br>5. DRAIN 1<br>6. GATE 2           | STYLE 8:<br>CANCELLED                                                                                  | STYLE 9:<br>PIN 1. EMITTER 2<br>2. EMITTER 1<br>3. COLLECTOR 1<br>4. BASE 1<br>5. BASE 2<br>6. COLLECTOR 2  | STYLE 10:<br>PIN 1. SOURCE 2<br>2. SOURCE 1<br>3. GATE 1<br>4. DRAIN 1<br>5. DRAIN 2<br>6. GATE 2           | STYLE 11:<br>PIN 1. CATHODE 2<br>2. CATHODE 2<br>3. ANODE 1<br>4. CATHODE 1<br>5. CATHODE 1<br>6. ANODE 2   | STYLE 12:<br>PIN 1. ANODE 2<br>2. ANODE 2<br>3. CATHODE 1<br>4. ANODE 1<br>5. ANODE 1<br>6. CATHODE 2 |
| STYLE 13:<br>PIN 1. ANODE<br>2. N/C<br>3. COLLECTOR<br>4. EMITTER<br>5. BASE<br>6. CATHODE                 | STYLE 14:<br>PIN 1. VREF<br>2. GND<br>3. GND<br>4. IOUT<br>5. VEN<br>6. VCC                            | STYLE 15:<br>PIN 1. ANODE 1<br>2. ANODE 2<br>3. ANODE 3<br>4. CATHODE 3<br>5. CATHODE 2<br>6. CATHODE 1     | STYLE 16:<br>PIN 1. BASE 1<br>2. EMITTER 2<br>3. COLLECTOR 2<br>4. BASE 2<br>5. EMITTER 1<br>6. COLLECTOR 1 | STYLE 17:<br>PIN 1. BASE 1<br>2. EMITTER 1<br>3. COLLECTOR 2<br>4. BASE 2<br>5. EMITTER 2<br>6. COLLECTOR 1 | STYLE 18:<br>PIN 1. VIN1<br>2. VCC<br>3. VOUT2<br>4. VIN2<br>5. GND<br>6. VOUT1                       |
| STYLE 19:<br>PIN 1. I OUT<br>2. GND<br>3. GND<br>4. V CC<br>5. V EN<br>6. V REF                            | STYLE 20:<br>PIN 1. COLLECTOR<br>2. COLLECTOR<br>3. BASE<br>4. EMITTER<br>5. COLLECTOR<br>6. COLLECTOR | STYLE 21:<br>PIN 1. ANODE 1<br>2. N/C<br>3. ANODE 2<br>4. CATHODE 2<br>5. N/C<br>6. CATHODE 1               | STYLE 22:<br>PIN 1. D1 (i)<br>2. GND<br>3. D2 (i)<br>4. D2 (c)<br>5. VBUS<br>6. D1 (c)                      | STYLE 23:<br>PIN 1. Vn<br>2. CH1<br>3. Vp<br>4. N/C<br>5. CH2<br>6. N/C                                     | STYLE 24:<br>PIN 1. CATHODE<br>2. ANODE<br>3. CATHODE<br>4. CATHODE<br>5. CATHODE<br>6. CATHODE       |
| STYLE 25:<br>PIN 1. BASE 1<br>2. CATHODE<br>3. COLLECTOR 2<br>4. BASE 2<br>5. EMITTER<br>6. COLLECTOR 1    | STYLE 26:<br>PIN 1. SOURCE 1<br>2. GATE 1<br>3. DRAIN 2<br>4. SOURCE 2<br>5. GATE 2<br>6. DRAIN 1      | STYLE 27:<br>PIN 1. BASE 2<br>2. BASE 1<br>3. COLLECTOR 1<br>4. EMITTER 1<br>5. EMITTER 2<br>6. COLLECTOR 2 | STYLE 28:<br>PIN 1. DRAIN<br>2. DRAIN<br>3. GATE<br>4. SOURCE<br>5. DRAIN<br>6. DRAIN                       | STYLE 29:<br>PIN 1. ANODE<br>2. ANODE<br>3. COLLECTOR<br>4. EMITTER<br>5. BASE/ANODE<br>6. CATHODE          | STYLE 30:<br>PIN 1. SOURCE 1<br>2. DRAIN 2<br>3. DRAIN 2<br>4. SOURCE 2<br>5. GATE 1<br>6. DRAIN 1    |

Note: Please refer to datasheet for style callout. If style type is not called out in the datasheet refer to the device datasheet pinout or pin assignment.

|                  |                             |                                                                                                                                                                                     |
|------------------|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DOCUMENT NUMBER: | 98ASB42985B                 | Electronic versions are uncontrolled except when accessed directly from the Document Repository.<br>Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION:     | SC-88 2.00x1.25x0.90, 0.65P | PAGE 2 OF 2                                                                                                                                                                         |





onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.


**TSOP-5 3.00x1.50x0.95, 0.95P**


CASE 483

ISSUE P

DATE 01 APR 2024


**GENERIC MARKING DIAGRAM\***


Analog



Discrete/Logic

XXX = Specific Device Code

A = Assembly Location

Y = Year

W = Work Week

▪ = Pb-Free Package

(Note: Microdot may be in either location)

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

XXX = Specific Device Code



M = Date Code

▪ = Pb-Free Package

## NOTES:

1. DIMENSIONING AND TOLERANCING CONFORM TO ASME Y14.5-2018.
2. ALL DIMENSION ARE IN MILLIMETERS (ANGLES IN DEGREES).
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS D AND E1 DO NOT INCLUDE MOLD FLASH, PROTRUSIONS OF GATE BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.15 PER SIDE. DIMENSION D.
5. OPTIONAL CONSTRUCTION: AN ADDITIONAL TRIMMED LEAD IS ALLOWED IN THIS LOCATION. TRIMMED LEAD NOT TO EXTEND MORE THAN 0.2 FROM BODY.

| DIM | MILLIMETERS |       |       |
|-----|-------------|-------|-------|
|     | MIN.        | NOM.  | MAX.  |
| A   | 0.900       | 1.000 | 1.100 |
| A1  | 0.010       | 0.055 | 0.100 |
| A2  | 0.950 REF.  |       |       |
| b   | 0.250       | 0.375 | 0.500 |
| c   | 0.100       | 0.180 | 0.260 |
| D   | 2.850       | 3.000 | 3.150 |
| E   | 2.500       | 2.750 | 3.000 |
| E1  | 1.350       | 1.500 | 1.650 |
| e   | 0.950 BSC   |       |       |
| L   | 0.200       | 0.400 | 0.600 |
| θ   | 0°          | 5°    | 10°   |


**RECOMMENDED MOUNTING FOOTPRINT\***

\* FOR ADDITIONAL INFORMATION ON OUR Pb-FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ON SEMICONDUCTOR SOLDERING AND MOUNTING TECHNIQUES REFERENCE MANUAL, SOLDERM/D.

**DOCUMENT NUMBER:** 98ARB18753C

Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.

**DESCRIPTION:** TSOP-5 3.00x1.50x0.95, 0.95P

**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.











SCALE 2:1


**UDFN8, 2x2**  
**CASE 517AW**  
**ISSUE A**

DATE 13 NOV 2015


**RECOMMENDED**  
**SOLDERING FOOTPRINT\***

**NOTES:**

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION b APPLIES TO PLATED TERMINALS AND IS MEASURED BETWEEN 0.15 AND 0.30 MM FROM THE TERMINAL TIP.
4. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.
5. FOR DEVICE OPN CONTAINING W OPTION, DETAIL B ALTERNATE CONSTRUCTION IS NOT APPLICABLE.

| DIM | MILLIMETERS |      |
|-----|-------------|------|
|     | MIN         | MAX  |
| A   | 0.45        | 0.55 |
| A1  | 0.00        | 0.05 |
| A3  | 0.13        | REF  |
| b   | 0.18        | 0.30 |
| D   | 2.00        | BSC  |
| D2  | 1.50        | 1.70 |
| E   | 2.00        | BSC  |
| E2  | 0.80        | 1.00 |
| e   | 0.50        | BSC  |
| L   | 0.20        | 0.45 |
| L1  | ---         | 0.15 |

**GENERIC**  
**MARKING DIAGRAM\***


- XX = Specific Device Code  
M = Date Code  
▪ = Pb-Free Package


(Note: Microdot may be in either location)

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present.

\*For additional information on our Pb-Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

|                         |                    |                                                                                                                                                                                  |
|-------------------------|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98AON34462E</b> | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>UDFN8, 2X2</b>  | <b>PAGE 1 OF 1</b>                                                                                                                                                               |


onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.



SCALE 2:1


Micro8  
CASE 846A-02  
ISSUE K

DATE 16 JUL 2020




TOP VIEW

NOTE 3




SIDE VIEW



END VIEW

GENERIC  
MARKING DIAGRAM\*




XXXX = Specific Device Code  
A = Assembly Location  
Y = Year  
W = Work Week  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2009.
2. CONTROLLING DIMENSION: MILLIMETERS
3. DIMENSION b DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE PROTRUSION SHALL BE 0.10 mm IN EXCESS OF MAXIMUM MATERIAL CONDITION.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSION OR GATE BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.15 mm PER SIDE. DIMENSION E DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.25 mm PER SIDE. DIMENSIONS D AND E ARE DETERMINED AT DATUM F.
5. DATUMS A AND B ARE TO BE DETERMINED AT DATUM F.
6. A1 IS DEFINED AS THE VERTICAL DISTANCE FROM THE SEATING PLANE TO THE LOWEST POINT ON THE PACKAGE BODY.



RECOMMENDED  
MOUNTING FOOTPRINT

For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERM-10.

| DIM | MILLIMETERS |      |      |
|-----|-------------|------|------|
|     | MIN.        | NOM. | MAX. |
| A   | ---         | ---  | 1.10 |
| A1  | 0.05        | 0.08 | 0.15 |
| b   | 0.25        | 0.33 | 0.40 |
| c   | 0.13        | 0.18 | 0.23 |
| D   | 2.90        | 3.00 | 3.10 |
| E   | 2.90        | 3.00 | 3.10 |
| e   | 0.65 BSC    |      |      |
| HE  | 4.75        | 4.90 | 5.05 |
| L   | 0.40        | 0.55 | 0.70 |

STYLE 1:

- PIN 1. SOURCE
- SOURCE
- SOURCE
- GATE
- DRAIN
- DRAIN
- DRAIN
- DRAIN

STYLE 2:


- PIN 1. SOURCE 1
- GATE 1
- SOURCE 2
- GATE 2
- DRAIN 2
- DRAIN 2
- DRAIN 1
- DRAIN 1

STYLE 3:

- PIN 1. N-SOURCE
- N-GATE
- P-SOURCE
- P-GATE
- P-DRAIN
- P-DRAIN
- N-DRAIN
- N-DRAIN


|                  |             |                                                                                                                                                                                  |
|------------------|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DOCUMENT NUMBER: | 98ASB14087C | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION:     | MICRO8      | PAGE 1 OF 1                                                                                                                                                                      |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.


**TSSOP-14 WB**  
CASE 948G  
ISSUE C


DATE 17 FEB 2016

SCALE 2:1



**NOTES:**

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH OR GATE BURRS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
4. DIMENSION B DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.25 (0.010) PER SIDE.
5. DIMENSION K DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 (0.003) TOTAL IN EXCESS OF THE K DIMENSION AT MAXIMUM MATERIAL CONDITION.
6. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
7. DIMENSION A AND B ARE TO BE DETERMINED AT DATUM PLANE -W-.

| DIM | MILLIMETERS |      | INCHES    |       |
|-----|-------------|------|-----------|-------|
|     | MIN         | MAX  | MIN       | MAX   |
| A   | 4.90        | 5.10 | 0.193     | 0.200 |
| B   | 4.30        | 4.50 | 0.169     | 0.177 |
| C   | ---         | 1.20 | ---       | 0.047 |
| D   | 0.05        | 0.15 | 0.002     | 0.006 |
| F   | 0.50        | 0.75 | 0.020     | 0.030 |
| G   | 0.65 BSC    |      | 0.026 BSC |       |
| H   | 0.50        | 0.60 | 0.020     | 0.024 |
| J   | 0.09        | 0.20 | 0.004     | 0.008 |
| J1  | 0.09        | 0.16 | 0.004     | 0.006 |
| K   | 0.19        | 0.30 | 0.007     | 0.012 |
| K1  | 0.19        | 0.25 | 0.007     | 0.010 |
| L   | 6.40 BSC    |      | 0.252 BSC |       |
| M   | 0°          | 8°   | 0°        | 8°    |

**RECOMMENDED  
SOLDERING FOOTPRINT\***


\*For additional information on our Pb-Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

**GENERIC  
MARKING DIAGRAM\***


A = Assembly Location  
L = Wafer Lot  
Y = Year  
W = Work Week  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

**DOCUMENT NUMBER:** 98ASH70246A

Electronic versions are uncontrolled except when accessed directly from the Document Repository.  
Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.

**DESCRIPTION:** TSSOP-14 WB

**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)