

Features

- Meets the Requirements of TIA/EIA- 232-F and ITU V.28 Standards
- Wide Power Supply Range: Single +3 V to +5.5 V
- Three Drivers and Five Receivers
- Operates up to 1 Mbps
- Low Standby Current: 1uA typical
- Requires Only Four External 0.1-μF Capacitors
- Auto-Power down Feature to Disable Driver Outputs When No Valid RS-232 Signal is Detected
- ESD Protection for RS-232 Bus Pins
 - ±18 kV (HBM)
 - ±20 kV (IEC61000-4-2, Contact Discharge)
 - ±25 kV (IEC61000-4-2, Air-Gap Discharge)

Applications

- Battery-Powered Equipment
- Industry Human Machine Interface
- Notebook, Computers
- Servers
- Printers

Description

The TPT3243 is ±20-kV IEC61000-4-2 contact ESD protected, 3.0-V to 5.5-V powered transceivers that meet the RS-232 standards for balanced communication. Each receiver converts TIA/RS-232 inputs to TTL/CMOS levels.

The charge pump and external capacitors support the device operating from a single 3.0-V to 5.5-V power supply. The device has an always-active output ROUT2B, which allows applications using the ring indicator to transmit data as the device is powered down.

The auto power-down function supports the ultra-low power mode. As the $\overline{\text{ONLINE}}$ is low and $\overline{\text{OFF}}$ is high, the driver outputs are disabled while the device does not sense a valid RS-232 signal. If $\overline{\text{OFF}}$ is set low, both drivers and receivers (except ROUT2B) are disabled, and the supply current is down to 1 μA.

The devices have a typical threshold of 1.25 V, a typical hysteresis of 0.3 V, and can accept ±25-V inputs. The device operates at data signaling rates up to 1 Mbps. The TPT3243 is available in TSSOP28, SSOP28, SOP28, and QFN32 packages, and is characterized from -40°C to 125°C.

Device Table

Device	Package	Body size
TPT3243-SS6R	SSOP28	10.2 mm x 5.3 mm
TPT3243-SO5R	SOP28	18.0 mm x 7.5 mm
TPT3243-TS6R	TSSOP28	9.8 mm x 4.4 mm
TPT3243-QFZR	QFN5X5-32	5.0 mm x 5.0 mm

Typical Application Circuit




Table of Contents


Features	1
Applications	1
Description	1
Device Table	1
Typical Application Circuit	2
Revision History	4
Pin Configuration and Functions	5
Specifications	7
Absolute Maximum Ratings ⁽¹⁾	7
ESD, Electrostatic Discharge Protection.....	7
Recommended Operating Conditions.....	8
Thermal Information.....	8
Electrical Characteristics.....	9
Electrical Characteristics - Timing Parameters.....	10
Electrical Characteristics - Auto Power Down.....	11
Typical Performance Characteristics.....	12
Detailed Description	14
Overview.....	14
Functional Block Diagram.....	14
Parameter Measurement Information.....	15
Application and Implementation	16
Typical Application.....	16
Layout	17
Layout Guideline.....	17
Layout Example.....	18
Tape and Reel Information	19
Package Outline Dimensions	20
SOP28.....	20
TSSOP28.....	21
SSOP28.....	22
QFN5X5-32.....	23
Order Information	24
IMPORTANT NOTICE AND DISCLAIMER	25

Revision History


Date	Revision	Notes
2024-04-19	Rev. A.0	Released version

Pin Configuration and Functions

TPT3243
SOP28/TSSOP28/SSOP28 Package
Top View



TPT3243
QFN5X5-32
Top View



3-V to 5.5-V, 1-Mbps Multi-Channel RS-232 Transceiver
Table 1. Pin Functions: TPT3243

Pin		Name	I/O	Description
SOP/ SSOP /TSSOP	QFN			
1	29	C2+		Positive lead of C2 capacitor
2	30	C2-		Negative lead of C2 capacitor
3	31	V-	Output	Negative charge pump output for storage capacitor only
4-8	1-5	RINx	Input	Input of RS232 receiver, RS232 level
9-11	6-8	TOUTx	Output	Output of RS232 driver, RS232 level
12-14	10-12	TINx	Input	The input of the RS232 driver, TTL/CMOS level
15-19	13-15, 17,18	ROUTx	Output	Output of RS232 receiver, TTL/CMOS level
20	19	ROUT2B	Output	TTL/CMOS Noninverting Complementary Receiver Output. Always active.
21	20	$\overline{\text{INVALID}}$	Output	Output of the Valid Signal Detector. /INVALID is enabled high if a valid RS-232 level is present on any receiver input.
22	21	$\overline{\text{OFF}}$	Input	$\overline{\text{OFF}}$ Input, active low. Drive low to shut down transmitters, receivers (except ROUT2B), and on-board charge pump
23	22	$\overline{\text{ONLINE}}$	Input	Active low. High level to drive normal working, low level to enable auto power down function ($\overline{\text{OFF}}$ must be high)
24	23	C1-		Negative lead of C1 capacitor
25	24	GND		Ground
26	26	VCC		Supply voltage
27	27	V+	Output	Positive charge pump output for storage capacitor only
28	28	C1+		Positive lead of C1 capacitor
	9,16,25,3 2	NC		Not connected internally
-		Thermal pad		Connect to GND internally

Specifications

Absolute Maximum Ratings ⁽¹⁾

Parameter		Min	Max	Unit
V _{CC}	Supply Voltage	-0.3	6	V
V+	Positive Output Supply Voltage	-0.3	7	V
V-	Negative Output Supply Voltage	-7	0.3	V
V+ - V-	Supply Voltage Difference		13	V
T _{INx}	Input Voltage of Driver, TTL/CMOS Level	-0.3	6	V
T _{OUTx}	Output Voltage of Driver, RS232 Level	-13.2	+13.2	V
R _{INx}	Input Voltage of Receiver, RS232 Level	-28	+28	V
R _{OUTx}	Output Voltage of Receiver, TTL/CMOS Level	-0.3	VCC +0.3	V
T _J	Operating Virtual Junction Temperature		150	°C

(1) Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. Exposure to any Absolute Maximum Rating condition for extended periods may affect device reliability and lifetime.

(2) This data was taken with the JEDEC low effective thermal conductivity test board.

(3) This data was taken with the JEDEC standard multilayer test boards.

ESD, Electrostatic Discharge Protection

Symbol	Parameter	Condition	Value	Unit
IEC	IEC Contact Discharge	IEC-61000-4-2, Bus Pin: TOUTx, RINx	±20	kV
	IEC Air-Gap Discharge	IEC-61000-4-2, Bus Pin: TOUTx, RINx	±25	kV
HBM	Human Body Model ESD ⁽¹⁾	ANSI/ESDA/JEDEC JS-001, Bus Pin: TOUTx, RINx	±18	kV
		ANSI/ESDA/JEDEC JS-001, All Pin	±7	kV
CDM	Charged Device Model ESD ⁽²⁾	ANSI/ESDA/JEDEC JS-002, All Pin	±1.5	kV
LU	Latch-up	LU, per JESD78, All Pin ⁽³⁾	±400	mA

(1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.

(2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

(3) Test at the temperature of 25°C.

Recommended Operating Conditions

Parameter		Min	Max	Unit
V _{CC}	Power Supply	3.0	5.5	V
V _{IH(TXD)}	Driver High-Level Input Voltage, V _{CC} = 5 V	2.4	5.5	V
	Driver High-Level Input Voltage, V _{CC} = 3.3 V	2	5.5	V
V _{IL(TXD)}	Driver Low-Level Input Voltage		0.8	V
V _I	Receiver Input Voltage	-25	25	V
T _A	Operating Ambient Temperature	-40	125	°C

Thermal Information

Package Type	θ_{JA}	θ_{JC}	Unit
SSOP28	82	41	°C/W
TSSOP28	75	26	°C/W
SOP28	63	32	°C/W
QFN32	40	31	°C/W

3-V to 5.5-V, 1-Mbps Multi-Channel RS-232 Transceiver
Electrical Characteristics

All test conditions: $V_{CC} = 3.0\text{ V to }5.5\text{ V}$, $T_A = -40^\circ\text{C to }125^\circ\text{C}$, unless otherwise noted.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
I_I	Input Leakage Current	$\overline{\text{OFF}}, \overline{\text{ONLINE}}$	-1		1	μA
I_{CC}	$I_{CC} = \text{Supply Current, Auto-Power Down Disabled}$	no load, $\overline{\text{ONLINE}} = \overline{\text{OFF}} = V_{CC}$, $TINx = \text{GND or } V_{CC}$		0.38	1	mA
	Auto-Power Down Enabled	no load, $\overline{\text{OFF}} = V_{CC}$, $\overline{\text{ONLINE}} = \text{GND}$, all $RINx$ are open, all $TINx$ are grounded		1.7	10	μA
	Powered off	No load, $\overline{\text{OFF}} = \text{GND}$		1.8	10	μA
Driver (TX)						
V_{IH}	Input Voltage of Logic High	$TINx, V_{CC} = 3.3\text{ V}$	2			V
		$TINx, V_{CC} = 5.0\text{ V}$	2.4			V
V_{IL}	Input Voltage of Logic Low	$TINx, V_{CC} = 3.3\text{ V}$			0.8	V
		$TINx, V_{CC} = 5.0\text{ V}$			0.8	V
I_{IH}	High-Level Input Current	$TINx, VIN = V_{CC}$	-1		1	μA
I_{IL}	Low-Level Input Current	$TINx, VIN = 0\text{ V}$	-1		1	μA
V_{OH}	Output High Voltage	$TOUT$ at $RL=3\text{ k}\Omega$ to GND	5.0	5.4		V
V_{OL}	Output Low Voltage	$TOUT$ at $RL=3\text{ k}\Omega$ to GND		-5.4	-5.0	V
I_{OS}	Output Short-Circuit Current ⁽¹⁾	$VOUT = 0\text{ V}$	-60		60	mA
I_{OFF}	Output Leakage Current	$\overline{\text{OFF}} = \text{GND}$, $V_o = 12\text{ V}$, $V_{CC} = 5.5\text{ V}$	-25		25	μA
R_o	Output Resistance ^{(1) (2)}	$V_{CC} = V_+ = V_- = 0\text{ V}$, $TOUTx = \pm 2\text{ V}$	0.3	1500		$\text{k}\Omega$
Receiver (RX)						
V_I	Receiver Input Voltage ⁽¹⁾		-25		25	V
V_{OL}	Output Voltage Low	$IOUT = 1.5\text{ mA}$			0.3	V
V_{OH}	Output Voltage High ⁽³⁾	$IOUT = -1.5\text{ mA}$	$V_{CC}-0.5$			V
V_{TH-}	Input Threshold Low	$V_{CC} = 3.3\text{ V}$	0.6	1.2		V
		$V_{CC} = 5.0\text{ V}$	0.8	1.5		V
V_{TH+}	Input Threshold High	$V_{CC} = 3.3\text{ V}$		1.5	2.4	V
		$V_{CC} = 5.0\text{ V}$		1.8	2.4	V
V_{hys}	Input Hysteresis ⁽¹⁾			0.3		V
I_{OFF}	Output Leakage Current (except $ROUT2B$)	$\overline{\text{OFF}} = \text{GND}$, $V_o = 12\text{ V}$, $V_{CC} = 5.5\text{ V}$	-10		10	μA
R_I	Input Resistance ^{(1) (2)}	$VI = \pm 3\text{ V or } \pm 25\text{ V}$	3	5	7	$\text{k}\Omega$

(1) Test data based on bench test and design simulation ; NOT test in production.

(2) Typ data is based on bench test by LRC meter E4980AL.

(3) $V_{CC} = 5\text{ V}$, $RX\ V_{OH} \geq V_{CC}-0.3\text{ V}$; $V_{CC} = 3.3\text{ V}$, $RX\ V_{OH} \geq V_{CC}-0.5\text{ V}$

Electrical Characteristics - Timing Parameters

All test conditions: $V_{CC} = 3.0\text{ V to }5.5\text{ V}$, $T_A = -40^{\circ}\text{C to }125^{\circ}\text{C}$, unless otherwise noted.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$f_{\max}$	Maximum Data Rate ⁽¹⁾	$R_L = 3\text{ k}\Omega$, $C_L = 1000\text{ pF}$, one driver switching ⁽¹⁾		1		Mbps
t_{DPLH}	Driver Propagation Delay, high to low output, t_{DPLH}	Driver input to Driver output, $C_L = 150\text{ pF}$		100	300 ⁽¹⁾	ns
t_{DPLH}	Driver Propagation Delay, low to high output, t_{DPLH}	Driver input to Driver output, $C_L = 150\text{ pF}$		100	300 ⁽¹⁾	ns
t_{Dsk}	Driver Skew ⁽¹⁾	$ t_{DPLH} - t_{DPLH} $		20		ns
SR_{tr}	Transition-Region Slew Rate	$V_{CC} = 3.3\text{ V}$, $R_L = 3\text{ k}\Omega$, $C_L = 1000\text{ pF}$, $T_A = 25^{\circ}\text{C}$ ⁽¹⁾	15	75	150	V/ μs
t_{RPHL}	Receiver Propagation Delay, high to low output, t_{RPHL}	Receiver input to receiver output, $C_L = 150\text{ pF}$		190	300 ⁽¹⁾	ns
t_{RPLH}	Receiver Propagation Delay, low to high output, t_{RPLH}	Receiver input to receiver output, $C_L = 150\text{ pF}$		130	300 ⁽¹⁾	ns
t_{Rsk}	Receiver Skew ⁽¹⁾	$ t_{DPLH} - t_{DPLH} $		60	100 ⁽¹⁾	ns
t_{en}	Output Enable Time			100	200 ⁽¹⁾	ns
t_{dis}	Output Disable Time			200	400 ⁽¹⁾	ns

(1) Test data is based on bench test and design simulation; NOT test in production.

Electrical Characteristics - Auto Power Down

All test conditions: $V_{CC} = 3.0\text{ V to }5.5\text{ V}$, $T_A = -40^{\circ}\text{C to }125^{\circ}\text{C}$, unless otherwise noted.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
V_{valid}	Receiver Input Voltage for Valid RS232 Level		-2.7		2.7	V
V_{invalid}	Receiver Input Voltage for Invalid RS232 Level		-0.3		0.3	V
V_{OH}	$\overline{\text{INVALID}}$ Output High Voltage	$\text{IOH} = -1.5\text{ mA}$	$V_{CC}-0.3$			V
V_{OL}	$\overline{\text{INVALID}}$ Output LOW Voltage	$\text{IOL} = 1.5\text{ mA}$			0.3	V
T_{valid}	Propagation Delay, Receiver Threshold to $\overline{\text{INVALID}}$ High ⁽¹⁾			1		μs
T_{invalid}	Propagation Delay, Receiver Threshold to $\overline{\text{INVALID}}$ Low ⁽¹⁾			30		μs
T_{online}	Propagation Delay, Receiver Threshold to Driver Enabled ⁽¹⁾			100		μs

(1) Test data is based on bench test and design simulation, NOT test in production.

Typical Performance Characteristics




Figure 1. TOUT_VOH(V) vs TOUT Current (mA)




Figure 2. TOUT_VOL(V) vs TOUT Current (mA)




Figure 3. Driver Skew (ns) per VCC(V) with C_{Load}




Figure 4. Output Voltage(V) per VCC(V)




Figure 5. Receiver TPHL(ns) per Temperature(°C)




Figure 6. Receiver TPLH(ns) per Temperature(°C)


3-V to 5.5-V, 1-Mbps Multi-Channel RS-232 Transceiver


Figure 7. Receiver Skew(ns) per Temperature(°C)

Detailed Description

Overview

The TPT3243 is $\pm 20\text{kV}$ IEC61000-4-2 contact ESD protected, 3.0-V to 5.5-V powered transceivers that meet the RS-232 standards for balanced communication. Each receiver converts TIA/RS-232 inputs to TTL/CMOS levels.

The charge pump and external capacitors support the device operating from a single 3.0-V to 5.5-V power supply. The device has an always-active output ROUT2B, which allows applications using the ring indicator to transmit data as the device is powered down.

The auto power-down function supports the ultra-low power mode. As the $\overline{\text{ONLINE}}$ is low and $\overline{\text{OFF}}$ is high, the driver outputs are disabled while the device does not sense a valid RS-232 signal. If $\overline{\text{OFF}}$ is set low, both drivers and receivers (except ROUT2B) are disabled, and the supply current is down to 1 μA .

The devices have a typical threshold of 1.25 V, a typical hysteresis of 0.3 V, and can accept $\pm 25\text{-V}$ inputs. The device operates at data signaling rates up to 1 Mbps. The TPT3243 is available in TSSOP28, SSOP28, SOP28, and QFN32 packages, and is characterized from -40°C to 125°C .

Functional Block Diagram





Figure 8. Functional Block Diagram

Parameter Measurement Information

Figure 9. Receiver Propagation Delay and Receiver Skew

Application and Implementation

Note

Information in the following application sections is not part of the 3PEAK's component specification and 3PEAK does not warrant its accuracy or completeness. 3PEAK's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

Typical Application




Figure 10. Typical Application Circuit

Non-polarized ceramic capacitors are acceptable. If polarized tantalum or electrolytic capacitors are used, they should be connected as shown in Figure 10. The recommended capacitor value of C1 to C4 is in Table 2. All cap is 0.1 µF for TPT3243.

Table 2. Required Minimum Capacitor Values

V _{CC} (V)	C1(µF)	C2, C3, C4(µF)
3.0 to 3.6	0.1	0.1
4.5 to 5.5	0.047	0.33
3.0 to 5.5	0.1	0.47

Layout

Layout Guideline

Reflections and matching are closely related to loop antenna theory, but different enough to warrant their discussion. When a PCB trace turns a corner at a 90° angle, a reflection can occur. This is primarily due to the change in the width of the trace. At the apex of the turn, the trace width is increased to 1.414 times its width. This change in width upsets the transmission line characteristics, especially the distributed capacitance and self-inductance of the trace, thus resulting in the reflection. Not all PCB traces can be straight, so they will have to turn corners. Figure 11 shows progressively better techniques of rounding corners. Only the last example (BEST) maintains constant trace width and minimizes reflections.




Figure 11. Trace Example

Route high-speed signals using a minimum of vias and corners which reduces signal reflections and impedance changes. When a via must be used, increase the clearance size around it to minimize its capacitance. Each via introduces discontinuities in the transmission line of the signal and increases the chance of picking up interference from the other layers of the board. Be careful when designing test points, through-hole pins are not recommended at high frequencies.

Layout Example

Figure 12 shows the location of external components as they appear on the PCB diagram.






Figure 12. Layout Example Diagram


Tape and Reel Information







Order Number	Package	D1 (mm)	A0 (mm)	K0 (mm)	W0 (mm)	W1 (mm)	B0 (mm)	P0 (mm)	Pin1 Quadrant
TPT3243-SO5R	SOP28	330	10.8	3.05	24.0	30.4	18.6	12.0	Q1
TPT3243-TS6R	TSSOP28	330	6.8	1.6	16.0	21.6	10.15	8.0	Q1
TPT3243-SS6R	SSOP28	330	8.2	2.34	16.0	21.6	10.5	12.0	Q1
TPT3243-QFZR	QFN32L	330	5.3	1.1	12.0	17.6	5.3	8.0	Q2

Package Outline Dimensions

SOP28





TSSOP28
Package Outline Dimensions
TS6(TSSOP-28-A)


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	0.900	1.200	0.035	0.047
A1	0.050	0.150	0.002	0.006
A2	0.800	1.050	0.031	0.041
b	0.190	0.300	0.007	0.012
c	0.090	0.200	0.004	0.008
D	9.600	9.800	0.378	0.386
E	6.200	6.600	0.244	0.260
E1	4.300	4.500	0.169	0.177
e	0.650 BSC		0.026 BSC	
L	0.450	0.750	0.018	0.030
θ	0	8°	0	8°

NOTES

1. Do not include mold flash or protrusion.
2. This drawing is subject to change without notice.

SSOP28
Package Outline Dimensions
SO5(SOP-28-A)

NOTES


1. Do not include mold flash or protrusion.
2. This drawing is subject to change without notice.

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	2.200	2.600	0.087	0.102
A1	0.100	0.300	0.004	0.012
A2	2.100	2.300	0.083	0.091
b	0.330	0.510	0.013	0.020
c	0.200	0.330	0.008	0.013
D	17.700	18.100	0.697	0.713
E	7.350	7.650	0.289	0.301
E1	10.100	10.500	0.398	0.413
e	1.270 BSC		0.050 BSC	
L	0.400	1.270	0.016	0.050
θ	0	8°	0	8°


QFN5X5-32

Package Outline Dimensions


QFZ(QFN5X5-32-I)



TOP VIEW



SIDE VIEW



BOTTOM VIEW

NOTES

1. Do not include mold flash or protrusion.
2. This drawing is subject to change without notice.
3. The many types of E-pad Pin1 signs may appear in the product.

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	0.700	0.800	0.028	0.031
A1	0.000	0.050	0.000	0.002
A3	0.180	0.250	0.007	0.010
b	0.180	0.300	0.007	0.012
D	4.900	5.100	0.193	0.201
E	4.900	5.100	0.193	0.201
e	0.400	0.600	0.157	0.236
D2	3.400	3.600	0.134	0.142
E2	3.400	3.600	0.134	0.142
L	0.300	0.450	0.012	0.018

Order Information

Order Number	Junction Temperature Range	Package	Marking Information	MSL	Transport Media, Quantity	Eco Plan
TPT3243-SO5R	-40 to 125°C	SSOP28	T3243	MSL3	Tape and Reel, 1500	Green
TPT3243-TS6R	-40 to 125°C	TSSOP28	T3243	MSL3	Tape and Reel, 4000	Green
TPT3243-SS6R	-40 to 125°C	SOP28	T3243	MSL3	Tape and Reel, 2000	Green
TPT3243-QFZR	-40 to 125°C	QFN5x5-32	T3243	MSL3	Tape and Reel, 3000	Green

Green: 3PEAK defines "Green" to mean RoHS compatible and free of halogen substances.

IMPORTANT NOTICE AND DISCLAIMER

Copyright© 3PEAK 2012-2024. All rights reserved.

Trademarks. Any of the 思瑞浦 or 3PEAK trade names, trademarks, graphic marks, and domain names contained in this document /material are the property of 3PEAK. You may NOT reproduce, modify, publish, transmit or distribute any Trademark without the prior written consent of 3PEAK.

Performance Information. Performance tests or performance range contained in this document/material are either results of design simulation or actual tests conducted under designated testing environment. Any variation in testing environment or simulation environment, including but not limited to testing method, testing process or testing temperature, may affect actual performance of the product.

Disclaimer. 3PEAK provides technical and reliability data (including data sheets), design resources (including reference designs), application or other design recommendations, networking tools, security information and other resources "As Is". 3PEAK makes no warranty as to the absence of defects, and makes no warranties of any kind, express or implied, including without limitation, implied warranties as to merchantability, fitness for a particular purpose or non-infringement of any third-party's intellectual property rights. Unless otherwise specified in writing, products supplied by 3PEAK are not designed to be used in any life-threatening scenarios, including critical medical applications, automotive safety-critical systems, aviation, aerospace, or any situations where failure could result in bodily harm, loss of life, or significant property damage. 3PEAK disclaims all liability for any such unauthorized use.

This page intentionally left blank